1 LOCATION OF WATER WELL:	FRACTION	Water Well Record	Form WWC-5	KSA 82a-1212 Section Number	Tarrest No. 37		ange Number
		WW CB	1/4	34	Township Number	R	112
Harvey Distance and direction from nearest town or city s	SW 1/4 treet address of well if locat	NW 1/4 SE	1/4	34	T 24 s	R	1W E/W
4th & Harrison, 1/2 W. of Ridge Rd. on E. side of Harrison Sedgwick, KS.							
	ICK, CITY		on E.	Side of	Hallison	BEUGWICK	, RS.
RRM, ST. ADRESS, BOX#: 511 N. Commercial Board of Agriculture, Divivsion of Water Resource							
	wick, Kans	as			Applica	ation Number: 96	0065
LOCATE WELL'S LOCATION WITH 4	DEPTH OF	WELL	50	ft. ELE	VATION:		
AN "X" IN SECTION BOX:	Depth(s) groundwa	ter Encountered	1	ft.		n. 3	ft.
	VELL'S STATIC WA	_		BELOW LAND SUR	FACE MEASURED ON I		21/1996
NWNE	Pump test					ours pumping	gpm
	st. Yield ore Hole Diameter U	gpm: Well was			after ho and	ours pumping	gpm ft.
	VELL WATER 1434		ublic water	ft. supply	and 8 Air conditioning	in. to 11 Injection	
	1 Domestic		Oil field wat	•	9 Dewatering	12 Other (Sp	
	2 Irrigation	4 Industrial 7 I	Lawn and ga	rden only 1	0 Monitoring well		
	Vas a chemical/bacte	riological sample subn	nitted to De	partment? Yes	No X	; If yes, mo/day/yr	sample was
S submitted Water Well Disinfected? Yes X No							
5 TYPE OF CASING USED:		5 Wrought iron		Concrete tile	CASING JOIN	Older.	Clamped
1 Steel 3 RMP (SR)		6 Asbestos-Cement	9 (Other (Specify b	elow)	Welded	
2 PVC 4 ABS		7 Fiberglass			_	Threaded	
	n. to	ft., Dia	in.	to	ft., Dia	in. to	ft.
Casing height the land surface 36 TYPE OF SCREEN OR PERFORAT!		weight	7	lbs. / ft. PVC	Wall thickness or gau 10 Asb	ge No. estos-cement	
& Filhanders & PRATICOD						/ B	
2 Brass 4 Galvanized steel 6 Concrete tile				9 ABS 12 None used (open hole)			
. ,						one (open hole)	
1 Continous slot 3 Mill slot 6 Wire wrapped					9 Drilled holes		
2 Louvered shutter 4 Key pun	7 Torch c	7 Torch cut		10 Other (specify) N/A		
SCREEN-PERFORATION INTERVA	LS: from	ft. to		ft., From	ı	ft. to	ft.
	from	ft. t	0	ft., From		ft. to	ft.
GRAVEL PACK INTERVALS: from		ft. to		ft., Fron		ft. to	ft.
from ft. to ft., From ft. to ft.						ft.	
6 GROUT MATERIAL: 1 Neat ce		ement grout	3 Ber	tonite	4 Other		
Grout Intervals: From 3 ft. to 6 What is the nearest source of possible contamination:		ft. From ft. to			ft. From vestock pens 12		o ft.
1 Septic tank 4 Lateral lines		7 Pit privy		11 Fuel storage		14 Abandon water well 15 Oil well/Gas well	
2 Sewer lines 5 Cess pool		8 Sewage lagoon		12 Fertilizer storage		16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit		9 Feedyard 13 Insecticid		cide storage	None A	pparent	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard None Apparent Direction from well?							
FROM TO L	ITHOLOGIC LOG		FROM	TO		NG INTERVALS	1.
			0		surface cl		.TC
			3			grout te hole plug	
			6 20		chlorinate		
			40	150	CHIOIIHACE	u sanu ar	ia graver
				71770			
	.,					-	
			-				
7 CONTRACTOR'S OR LANDOWNER							
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)							
Well Contractor's License No							
Under the business name of HarpWell.&PumpServiceInc							
					To	dd S. F	larp