				Water Well Reco	ord Form WWC-5	KSA 82a-1212			
1 LOCATI	ON OF WAT	ER WELL:	FRACTION			Section Number	Township Number	Range Number	
	larve		SW 1/4	NW 1/4	SE 1/4	34	T 24 s	R 1W E/W	
Distance an	d direction f	rem nearest town or cit	y street address of well if loc	ated within city?					
4tl	1 & H		1/2 W. of		on E.	side of	Harrison Sec	lgwick, KS.	
WATI	ER WELL O		WICK, CITY						
_	. ADRESS, I		N. Commerc				-	, Divivsion of Water Resource	
CITY, S	TATE, ZIP	code: Sed	wick, Kans				Application Num	aber: 960105	
	WELL'S LON	DCATION WITH		MGGCO WELL			EVATION:	_	
A	- I	N	Depth(s) groundw			ft.	2 ft.	3 ft.	
			WELL'S STATIC W				JRFACE MEASURED ON mo/day/yr		
	NW	NE	Pump tes		l water was	ft.	after hours po		
<u> </u>	i		Est. Yield	6 F	ll water was	ft.	after hours p		
M M		E	Bore Hole Diameter (to 5 Public wate	ft. n annah		n. to ft. 1 Injection well	
			1 Domestic	3 Feedlot	6 Oil field wa			2 Other (Specify below)	
1	sw	>	2 Irrigation	4 Industrial	7 Lawn and g		10 Monitoring well	2 Culei (Speelly Below)	
							•	No 🗶 ; If yes, mo/day/yr sample was	
		S	submitted	er rorogreat sample	sublinited to D	-		s X No	
5 TYP	E OF CA	SING USED:		5 Wrought iro	n 8	Concrete tile	CASING JOINTS:	Glued Clamped	
TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (Specify below) Welded									
2 PVC		4 ABS		7 Fiberglass				Threaded	
Blank cas	ing Diam	eter 5	in. to	ft. Dia	in.	to	ft., Dia in	. to ft.	
		e land surface	36 in.,	weight		lbs. / ft.	Wall thickness or gauge No.		
TYPE O	F SCREE	N OR PERFORA	TION MATERIAL:			7 PVC	10 Asbestos-co		
1 Steel		3 Stainless Steel		5 Fiberglass		RMP (SR)	11 other (spe	M/A	
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)								,	
SCREEN OR FERFORATION OF ENTRO ARE.								11 None (open hole)	
1 Continous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes									
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) N/A									
SCREEN	-PERFO	RATION INTER	VALS: from		ft. to	ft., Fro	m ft.	to ft.	
,			from		ft. to	ft., Fro	m ft.	to ft.	
GRAVEL PACK INTERVALS: from				ft. to		ft., Fro	m ft.	to ft.	
<u> </u>			from		ft. to	ft., Fro		to ft.	
	UT MAT	D2441	-	Cement grout	3 Be	ntonite	4 Other		
Grout Intervals: From 3 ft. to 8 ft. From ft. to ft.									
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy						10 Livestock pens 14 Abandon water well			
i -				8 Sewage lagoon		11 Fuel storage 12 Fertilizer storage		15 Oil well/Gas well	
2 Sewer lines 5 Cess pool 3 Watertight sewer lines 6 Seepage pi			•	9 Feedvard		13 Insecticide storage		16 Other (specify below)	
1	•	-	page pit	9 reedyan	u			ne Apparent	
FROM	rom we	17	LITHOLOGIC LOC	1	FROM	TO	How many feet? PLUGGING IN	TERVALS	
IROM	10		LITHOLOGIC DOC		0	3	surface clay		
					3	8	cement grout		
					8	15	bentonite hol	e plug	
					15	50	chlorinated s	and and grave:	
							- The Area		
								A CONTRACTOR OF THE PROPERTY O	
		·							
							A set of		
								, , , , , , , , , , , , , , , , , , ,	
		<u></u>							
7 CO	NTRACT	OR'S OR LANDOWN	ER'S CERTIFICATION:	This water well w	as (1) constru	cted, (2) recons	tructed, or (3) plugged und	ler my jurisdiction and	
was c	ompleted	on (mo/day/yea	ar)		and this re	ecord is true to	the best of my knowledge	and belief. Kansas Water	
Well C	ontracto	rs License No.	arp Well &	I nis water We	en Kecord Was rvice - T	nc hydei	(mo/day/yr)Ω.6.		
Unuer	uic DuSi	iicəə iidlik Ui.M	M		4.M.m.m.i	nà (si	9 1 / T	S. Haro	