1 LOCATION OF WATER WELL:	FRACTION	Water Well Record	Form WWC-5	KSA 82a-1212 Section Number	Tananak ta Marana		Panga Number	
<u>_</u>		WW CT	, "		Township Number		Range Number	
Harvey Distance and direction from nearest town or cit	SW 1/4	NW 1/4 SE	1/4	34	т 24 s		R 1W E/W	
	•	•				~	1l. 250	
4th & Harrison, WATER WELL OWNER: SED	GWICK, CITY		on E.	side of	Harrison	Seagw	ick, KS.	
	N. Commerc				Board of	Agriculture, Diviv	sion of Water Resource	
	gwick, Kans					ication Number:	960065	
LOCATE WELL'S LOCATION WITH	DEPTH OF COM	AAC WELL	50	ft. EL	EVATION:		30000	
AN "X" IN SECTION BOX:	Depth(s) groundwa		1	ft.	2	ft.	3 ft.	
†	WELL'S STATIC WA	ATER LEVEL 14	FT.	BELOW LAND SU	RFACE MEASURED ON	mo/day/yr	06/21/1996	
NE.	Pump test	data: Well wa	ter was	ft.	after]	hours pumpir		
	Est. Yield	gpm: Well wa	ter was	ft.	after 1	hours pumpir		
E W	Bore Hole Diameter U	nknown in. to)	ft.	and	in.	to ft.	
= "	WELL WATER	USED AS: 51	Public water	supply	8 Air conditioning	11 Inje	ection well	
X X X X X X X X X	1 Domestic		Oil field wat		9 Dewatering	12 Oth	ner (Specify below)	
	2 Irrigation	4 Industrial 7	Lawn and g	arden only	10 Monitoring well			
S	Was a chemical/bacter	riological sample subr	nitted to De	_			day/yr sample was	
	submitted				ter Well Disinfected?			
5 TYPE OF CASING USED: 1 Steel 3 RMP (SR)	5 Wrought iron							
V 54.12 (02.5)	6 Asbestos-Cement 7 Fiberglass	9	Other (Specify	Delow)		ded eaded		
2 PVC 4 ABS		•						
Blank casing Diameter 8 Casing height hand surface	in. to	ft., Dia	in.	to lbs. / ft.	ft., Dia Wall thickness or ga		to ft.	
TYPE OF SCREEN OR PERFORA		weight	7	PVC		uge 140. bestos-cement	ŧ	
5 Vihousians O DATI (CD)							n/a	
2 Brass 4 Galvanized ste	el	6 Concrete tile	9	ABS	12 No	one used (oper		
SCREEN OR PERFORATION OP	5 Gauzeo	l wrapped		8 Saw cut 11 None (open hole)				
1 Continous slot 3 Mill slot		5 Gauzed wrapped 6 Wire wrapped			9 Drilled holes			
	ounched	7 Torch o	nit		10 Other (speci	fy) N/ /	A	
SCREEN-PERFORATION INTER	VALS: from	ft. t		ft., Fro	m	ft. to	ne. ft.	
,	from		-	ft., Fro		ft. to	ft.	
GRAVEL PACK INTERVALS: from		ft. to ft. to		ft., Fro				
from		ft. to		ft., Fro		ft. to		
6 GROUT MATERIAL: 1 Neat		ement grout		ntonite	4 Other			
Grout Intervals: From 3	ft. to 6	ft. From	ft.	to	ft. From		ft. to ft.	
What is the nearest source of possible contamination:		11 11011			10 Livestock pens		14 Abandon water well	
1 Septic tank 4 Lateral lines		7 Pit privy		11 Fuel s	torage	15 Oil well/Gas well		
2 Sewer lines 5 Cess pool		8 Sewage lagoon		12 Fertilizer storage		16 Other (specify below)		
3 Watertight sewer lines 6 Seepage pit		9 Feedyard 13 Insectic		icide storage None Apparent				
Direction from well?				How many feet	eet?			
FROM TO	LITHOLOGIC LOG		FROM	ТО		ING INTERV		
			0	3	surface c		silt	
			3	6	cement gro		1	
			6	20	bentonite		and gravel	
			20	50	Chiorinate	ed sand	and graver	
			 					
							Januarus	
7 CONTRACTOR'S OR LANDOWN	ER'S CERTIFICATION: Th	is water well was /1) construct	ed. (2) recons	tructed, or (3) plugg	ed under m	v jurisdiction and	
was completed on (mo/day/yea	r) Q6/21/	1996	and this re	cord is true to	the best of my know	wledge and b	pelief. Kansas Water	
Well Contractor's License No	236	This Water Well Re	cord was o	ompleted on (mo/day/yr)			
Under the business name of HarpWell.&PumpService								
i					\mathcal{I}_{c}	odd S.	. Harp	