

1 LOCATION OF WATER WELL: County: HARVEY		Fraction SW ¼ SE ¼ NE ¼		Section Number 5	Township Number T 24 S	Range Number R 1 E/W
Distance and direction from nearest town or city street address of well if located within city? 2 3/4 MILES EAST & 1/2 MILE SOUTH OF HALSTEAD, KANSAS						
2 WATER WELL OWNER: HORST PHARMACY INC. RR#, St. Address, Box # : 511 N. MAIN City, State, ZIP Code : NEWTON KS 67114 Board of Agriculture, Division of Water Resources Application Number: 2687						
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL 140 ft. ELEVATION: Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 19.67 ft. below land surface measured on mo/day/yr 1/18/94 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter in. to ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No				
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 16 in. to ft., Dia in. to ft., Dia in. to ft. Casing height BELOW land surface 48 in., weight lbs./ft. Wall thickness or gauge No. 3/16 INCH TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) NA 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes NA 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) NA SCREEN-PERFORATED INTERVALS: From NA ft. to NA ft., From ft. to ft. GRAVEL PACK INTERVALS: From ft. to ft., From ft. to ft. From ft. to ft., From ft. to ft.						
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 19.5 ft. to 3 ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Direction from well? NORTH-NORTHWEST How many feet? APPROXIMATELY 2640						
FROM	TO	LITHOLOGIC LOG		FROM	TO	PLUGGING INTERVALS
				140	19.5	SAND AND GRAVEL
				19.5	3.5	BENTONITE HOLEPLUG
				3.5	0	TOPSOIL
*PLUGGING WITNESSED BY DON KOCI, EQUUS BEDS GMD#2						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1/20/94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. N/A This Water Well Record was completed on (mo/day/yr) 1/23/94 under the business name of N/A by (signature) Ken Horst President						

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.