

1 LOCATION OF WATER WELL		Fraction	Section Number	Township Number	Range Number
County: <u>Haven</u>		<u>SW 1/4 NE 1/4 SW 1/4</u>	<u>34</u>	<u>T 24 S</u>	<u>R 1 E</u>
Distance and direction from nearest town or city?			Street address of well if located within city? <u>Edgemoor</u>		
2 WATER WELL OWNER: <u>1st Congregation Church</u>			Board of Agriculture, Division of Water Resources		
RR#, St. Address, Box #: <u>200 So. Main</u>			Application Number:		
City, State, ZIP Code: <u>Seagr. Wichita, KS.</u>					
3 DEPTH OF COMPLETED WELL: <u>20</u> ft. Bore Hole Diameter: <u>1.1</u> in. to ft., and in. to ft.					
Well Water to be used as:					
1 Domestic		3 Feedlot	5 Public water supply	8 Air conditioning	11 Injection well
2 Irrigation		4 Industrial	6 Oil field water supply	9 Dewatering	12 Other (Specify below)
		7 Lawn and garden only	10 Observation well		
Well's static water level: <u>19</u> ft. below land surface measured on month day year					
Pump Test Data: Well water was <u>23</u> ft. after <u>1/2</u> hours pumping. <u>15</u> gpm					
Est. Yield <u>30</u> gpm: Well water was ft. after hours pumping gpm					
4 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	5 Wrought iron	8 Concrete tile	Casing Joints: <u>Glued</u> Clamped
2 PVC		4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded
			7 Fiberglass		Threaded
Blank casing dia. <u>5</u> in. to <u>35</u> ft., Dia. in. to ft., Dia. in. to ft.					
Casing height above land surface: <u>12</u> in., weight <u>1.50</u> lbs./ft. Wall thickness or gauge No. <u>200</u>					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement
2 Brass		4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify)
					12 None used (open hole)
Screen or Perforation Openings Are:					
1 Continuous slot		3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter		4 Key punched	6 Wire wrapped	9 Drilled holes	
			7 Torch cut	10 Other (specify)	
Screen-Perforation Dia. <u>5</u> in. to <u>50</u> ft., Dia. in. to ft., Dia. in. to ft.					
Screen-Perforated Intervals: From <u>35</u> ft. to <u>50</u> ft., From ft. to ft., From ft. to ft.					
Gravel Pack Intervals: From <u>10</u> ft. to <u>60</u> ft., From ft. to ft., From ft. to ft.					
5 GROUT MATERIAL:					
1 Neat cement		2 Cement grout	3 Bentonite	4 Other	
Grouted Intervals: From <u>0</u> ft. to <u>10</u> ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Cess pool	7 Sewage lagoon	10 Fuel storage	14 Abandoned water well
2 Sewer lines		5 Seepage pit	8 Feed yard	11 Fertilizer storage	15 Oil well/Gas well
3 Lateral lines		6 Pit privy	9 Livestock pens	12 Insecticide storage	16 Other (specify below)
Direction from well: <u>SE</u> How many feet: <u>90</u> ? Water Well Disinfected? <u>Yes</u> No					
Was a chemical/bacteriological sample submitted to Department? Yes No If yes, date sample was submitted month day year: Pump Installed? Yes No					
If Yes: Pump Manufacturer's name Model No. HP Volts					
Depth of Pump Intake ft. Pumps Capacity rated at gal./min.					
Type of pump: 1 Submersible 2 Turbine 3 Jet 4 Centrifugal 5 Reciprocating 6 Other					
6 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on month day year					
and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>318</u>					
This Water Well Record was completed on month day year under the business name of <u>Wenger Drilling</u> by (signature) <u>James Wenger</u>					
7 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		LITHOLOGIC LOG		LITHOLOGIC LOG	
		FROM	TO	FROM	TO
		<u>0</u>	<u>2</u>	<u>TOP SOIL</u>	
		<u>2</u>	<u>16</u>	<u>Red clay</u>	
		<u>16</u>	<u>29</u>	<u>fine sand</u>	
		<u>29</u>	<u>50</u>	<u>Charcoal/Clay</u>	
ELEVATION:					
Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. 4. ft. (Use a second sheet if needed)					

OFFICE USE ONLY

T

24

R

1

EW

SEC

34

SW 1/4

NE 1/4

SW 1/4

SW 1/4