

1 LOCATION OF WATER WELL: County: HARVEY	Fraction SW 1/4 NW 1/4 SE 1/4	Section Number 34	Township Number T 24 S	Range Number R 1 E 10
--	---	-----------------------------	----------------------------------	---------------------------------

Distance and direction from nearest town or city street address of well if located within city?

280' South & 55' East of the Center of Commercial & Fifth St. Intersection

2 WATER WELL OWNER: Sedgwick Motors Inc.	MW-4
RR#, St. Address, Box # : 418 N. Commercial	Board of Agriculture, Division of Water Resources
City, State, ZIP Code : Sedgwick KS 67135	Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 30 ft. ELEVATION: 1374.13 TOC
	Depth(s) Groundwater Encountered 1. 21.2 ft. 2. . ft. 3. . ft.
	WELL'S STATIC WATER LEVEL 21.2 ft. below land surface measured on mo/day/yr 2/5/93
	Pump test data: Well water was . ft. after . hours pumping . gpm
	Est. Yield . gpm: Well water was . ft. after . hours pumping . gpm
	Bore Hole Diameter . in. to . ft., and . in. to . ft.
WELL WATER TO BE USED AS:	5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)	
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> If yes, mo/day/yr sample was submitted	Water Well Disinfected? Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>

5 TYPE OF BLANK CASING USED:	5 Wrought iron 8 Concrete tile CASING JOINTS: Glued . Clamped .
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded .	
2 PVC 4 ABS 7 Fiberglass Threaded	
Blank casing diameter . in. to . ft., Dia . in. to . ft., Dia . in. to . ft.	
Casing height above land surface Flush in., weight . lbs./ft. Wall thickness or gauge No. Sch 40	
TYPE OF SCREEN OR PERFORATION MATERIAL:	2 PVC 10 Asbestos-cement
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)	
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped 8 Saw cut 11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes	
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From . ft. to 29 ft., From . ft. to . ft.	
GRAVEL PACK INTERVALS: From 13 ft. to 30 ft., From . ft. to . ft.	

6 GROUT MATERIAL:	1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 1 ft. to 11 ft., From 11 ft. to 13 ft., From . ft. to . ft.	
What is the nearest source of possible contamination:	10 Livestock pens 14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well	
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage UST Excavation	
Direction from well?	How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	Concrete			
1	13	Clay, Dark Brown			
13	18	Sand, fine grained			
18	20	Sand, fine to medium			
20	30	Sand, medium to coarse			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2/3/93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 483 This Water Well Record was completed on (mo/day/yr) 3/18/93 under the business name of T.E.S.T. by (signature) David Lowry
--