		Water Well Record	Form WWC-5	KSA 82a-1212			
1 LOCATION OF WATER WELL:	FRACTION		·	Section Number	Township Number	Range Number	
Harvey	NE 1/4	NW 1/4 ST	W 1/4	34	_T 24 _s	R 1W E/W	
Distance and direction frem nearest town or city street address of well if located within city?							
711 N. Washington Sedgwick, Kansas							
WATER WELL OWNER: HOYT,	Cynthia	_					
RR#, ST. ADRESS, BOX#: 711 N. Washington Board of Agriculture, Divivsion of Water Resource							
CITY, STATE, ZIP CODE: Sedqwick, Kansas Application Number:							
LOCATE WELL'S LOCATION WITH 4	DEPTH OF COM	PLETED WELL	75	ft. ELEV	ATION:		
— AN "X" IN SECTION BOX:	Depth(s) groundwa	ter Encountered	1	ft.	2 ft.	3 ft.	
↑ wı	ELL'S STATIC WA	TER LEVEL 15	FT.	BELOW LAND SURI	FACE MEASURED ON mo/day/yr	06/17/1999	
NE NE	Pump test	data: Well wa	ater was	ft. at	fter hours pum	ping gpm	
Est	Yield	gpm: Well w	ater was	ft. a	fter hours pum	ping gpm	
E Bor	e Hole Diameter	12 in. t	o 75	ft.	and in.	to ft.	
= " X	LL WATER TO B	E USED AS: 5	Public water	supply 8	Air conditioning 11 I	njection well	
swse	1 Domestic		Oil field wat	ter supply 9	Dewatering 12 C	Other (Specify below)	
	2 Irrigation	4 Industrial 7	Lawn and g	arden only 10	Monitoring well		
↓ L L Wa	s a chemical/bacter	riological sample sub	mitted to De	_		io/day/yr sample was	
S submitted Water Well Disinfected? Yes X No							
5 TYPE OF CASING USED:		5 Wrought iron		Concrete tile		lued X Clamped	
1 Steel 3 RMP (SR)		6 Asbestos-Cement	9	Other (Specify bel	low) V	Velded	
2 PVC 4 ABS		7 Fiberglass	S	DR-26	T	`hreaded	
Blank casing Diameter 5 in.	to 35	ft., Dia	in.	to	ft., Dia in.	to ft.	
Casing height above land surface 12	in. ,	weight 2.	. 35	lbs. / ft. V	Vall thickness or gauge No.	.214	
TYPE OF SCREEN OR PERFORATIO	N MATERIAL:	# T7/1 1		PVC	10 Asbestos-ceme		
1 Steel 3 Stainless Steel		5 Fiberglass		RMP (SR)	11 other (specify	•	
2 Brass 4 Galvanized steel		6 Concrete tile	9	ABS	12 None used (or	•	
SCREEN OR PERFORATION OPENIN	IG ARE:	5 Gauze	d wrapped		8 Saw cut	11 None (open hole)	
1 Continous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes							
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)							
SCREEN-PERFORATION INTERVAL	6: from 35	ft. 1	to 4 5	ft., From	ft. to	ft.	
	from 65	ft.	to 75	ft., From	ft. to	ft.	
GRAVEL PACK INTERVALS: from 24		ft. to 75		ft., From	ft. to	ft.	
	from	ft.	to	ft., From	ft. to	ft.	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug							
	to 24	ft. From	ft.		ft. From 45	ft. to 47 ft.	
What is the nearest source of possible contamination:		= T04		10 Livestoc	-	14 Abandon water well	
1 Septic tank 4 Lateral lines		7 Pit privy		11 Fuel stor	130	15 Oil well/Gas well	
2 Sewer lines 5 Cess pool		8 Sewage lagoon		12 Fertilize 13 Insectici	2	16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage							
Direction from well? East					How many feet? 90		
	HOLOGIC LOG		FROM	ТО	PLUGGING INTE	RVALS	
0 3 topsoil							
3 18 clay			1	1			
18 32 fine sand							
32 45 dirty medi	<u>um sand</u>						
45 67 clay 67 70 fine sand			1	 			
70 75 grey shale				· · · · · · · · · · · · · · · · · · ·			
			1				
						,	
			<u> </u>	† †			
			1				
						MARKET 10 - 10 - 10 - 10 - 10 - 10 - 10 - 10	
			1				
7 CONTRACTIONS							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)							
was completed on (mo/day/year)	××	talalalalar Wall Da	and this red	ora is true to the	e best of my knowledge and N/day/yr)	Nellei. Kansas Water 8/99	
Under the husiness name of Hart	Well &	Pump Servi	ce, Ir	Chipieteu on (IRC LC hv /einna	//www.yr.yr.j	m.j	
Under the business name of Harp Well & Pump Service. Inc. by (signature) Todd S. Harp							
					C Guill X	·· vuy	