1 LOCATION O	OF WATER WELL:	FRACTION				9.	ection Number	Township Number	Range Number
اث	terrick HARVEY			1/4	gw .		34		1 TAT
			1/4 NW	1/4 n city?	SW 1	/4	J 4	T 24 s	R IW E/W
Distance and direction from nearest town or city street address of well if located within city?									
600 N. Commercial Ave. Sedgwick, Kansas WATER WELL OWNER: METHODIST CHURCH OF SEDGWICK									
					DGMTCF			Board of Agriculture	Divivsion of Water Resource
RR#, ST. ADRESS, BOX#: 600 N. Commercial Ave. CITY, STATE, ZIP CODE: Sedgwick, Kansas Application Number:									
	LL'S LOCATION WITH 4		COMPLET	ED WELL	45		ft. ELE	Application Numb	
AN "X" IN SE	CCTION BOX:		undwater En		, 4:5 1		ft.	VATION: 2 ft.	3 ft.
† F		ELL'S STAT			_	FT. REI		LFACE MEASURED ON mo/day/yr	08/25/1999
			IC WATER I np test data:		LO I water was			after hours pur	
	NW NE Est	t. Yield	gpm:		l water was Il water wa			after hours pu	
w W		re Hole Diam			to 45		ft.	and in.	
€ W	Y: 1 - 1 - 1	ELL WATER			5 Public v				Injection well
		1 Domestic			6 Oil field				Other (Specify below)
	SW SE	2 Irrigation	4 Ind	ustrial	7 Lawn a	nd gard	en only 1	0 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was								mo/day/yr sample was	
S submitted Water Well Disinfected? Yes X No									
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped									Glued X Clamped
1 Steel	3 RMP (SR)		6 Asbestos-Cement			her (Specify be	,	Welded	
2 PVC	4 ABS		7 Fib	erglass		SDR	2-26		Threaded
Blank casing	_	to 25	ft.,	, Dia		in.	to	ft., Dia in.	to ft.
	t above land surface 12		in.,		2.35			Wall thickness or gauge No.	.214
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement									
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify)									
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)									
SCREEN OR PERFORATION OPENING ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)									11 None (open hole)
1 Continous	J Willi Blot	had			ire wrapped			9 Drilled holes	
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)									
SCREEN-PERFORATION INTERVALS: from 25 ft. to 45 ft., From ft. to ft.									
	D. 4 T T T T T T T T T T T T T T T T T T	from	_		ft. to		ft., From		
GRAVEL PACK INTERVALS: from 25				ft. to 45			ft., From		
from ft. to ft., From ft. to ft.									
GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug Grout Intervals: From 4 ft. to 24 ft. From ft. to ft. From 24 ft. to 25 ft.									
What is the nearest source of possible contamination:				ft. From			10 Livesto	ft. From 24	ft. to 25 ft.
1 Septic tank 4 Lateral lines				7 Pit privy			11 Fuel sto		Abandon water well
2 Sewer lines 5 Cess pool				8 Sewage lagoon			11 Fuel storage 12 Fertilizer storage		5 Oil well/Gas well 6 Other (specify below)
3 Watertight sewer lines 6 Seepage pit				9 Feedvard			13 Insecticide storage		
Direction from well? East How many feet? 15									
		THOLOGIC	LOG		FRO	OM	то	PLUGGING INT	ERVALS
0 4	topsoil								
4 15	fine sand								
15 20	clay					\bot			
20 30						I			
30 40	coarse sa	nd				[
40 45	medium sa	nd							
									TO A LABOR TO THE PARTY OF THE
				-					
									
						-			
									
7 CONTR	ACTOR'S OR LANDOWNER'S	CERTIFICATION	ON: This wat	er well wa	as (1) <u>cons</u>	<u>tructe</u> d	, (2) reconstr	ructed, or (3) plugged unde	r my jurisdiction and
								he best of my knowledge a	
vveil Conti	LACTOR E LICONES NA				II P		anlata i	noldardes no/	27/44
Under the	business name of.Hax	m.w.w	This \ & Pijm	Nater We	∥Record v ∵vice	vas con Inc	npleted on (n	no/day/yr)0.8./	27/99