

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Harvey		SW 1/4 SW 1/4 NW 1/4		6		T 24 S		R 1 E	
Distance and direction from nearest town or city street address of well if located within city?									
Approximately 1 mile east of Halstead									
2 WATER WELL OWNER: Public Wholesale Water Supply District No. 17									
RR#, St. Address, Box # : P.O. Box 426									
City, State, ZIP Code : Newton, KS 67114									
Board of Agriculture, Division of Water Resources									
Application Number:									
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 140 ft. ELEVATION: unknown							
		Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft.							
		WELL'S STATIC WATER LEVEL 33.74 ft. below land surface measured on mo/day/yr 1-24-01							
		Pump test data: Well water was not ch'd ft. after hours pumping gpm							
		Est. Yield unknown gpm: Well water was ft. after hours pumping gpm							
		Bore Hole Diameter 9 in. to 140 ft., and in. to ft.							
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well									
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (specify below)									
2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well Test Well									
Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted									
Water Well Disinfected? Yes No									
5 TYPE OF BLANK CASING USED:									
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped									
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded									
Blank casing diameter 5 in. to 88 ft., Dia in. to ft., Dia in. to ft.									
Casing height above land surface 24 in., weight 2.36 lbs./ft. Wall thickness or gauge No .214									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement									
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)									
12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)									
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes									
3 Torch cut 10 Other (specify) ft.									
SCREEN-PERFORATED INTERVALS: From 88 ft. to 138 ft., From ft. to ft.									
GRAVEL PACK INTERVALS: From 60 ft. to 140 ft., From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Bentonite Holeplug									
Grout Intervals: From ft. to ft., From ft. to ft., From 0 ft. to 60 ft.									
What is the nearest source of possible contamination:									
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well									
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well									
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)									
None known									
Direction from well? How many feet?									
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS									
0 4 Topsoil									
4 16 Sand and gravel, medium, fine									
16 30 Clay, tan, hard									
30 47 Clay, tan, gravel streaks									
47 57 Clay, white, gravel streaks									
57 138 Sand and gravel, medium, fine, clay streaks									
138 140 Shale, black, hard									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-24-01 and this record is true to the best of my knowledge and belief. Kansas									
Water Well Contractor's License No 185 This Water Well Record was completed on (mo/day/yr) 1-26-01									
under the business name of Clarke Well & Equipment, Inc. by (signature)									