

1] LOCATION OF WATER WELL: County: <u>Harvey</u>	Fraction: <u>NW 1/4 NW 1/4 NW 1/4</u>	Section Number: <u>13</u>	Township Number: <u>T 24 S</u>	Range Number: <u>R 1 EW</u>
--	---------------------------------------	---------------------------	--------------------------------	-----------------------------

Distance and direction from nearest town or city street address of well if located within city?

See below

2] WATER WELL OWNER: <u>Rick Weibe</u>	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: <u>3401 SW 60th</u>	Application Number:
City, State, ZIP Code: <u>Sedgwick, KS 67135</u>	

3] LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4] DEPTH OF COMPLETED WELL: <u>36</u> ft. ELEVATION:
---	--

Diagram of a section box divided into four quadrants: NW, NE, SW, SE. An 'X' is marked in the NW quadrant. A north arrow is shown to the left of the box.

Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL: 17 ft. below land surface measured on mo/day/yr 1-8-02

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield: 20 gpm; Well water was ft. after hours pumping gpm

Bore Hole Diameter: 11 in. to 36 ft., and in. to ft.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial	7 Domestic (lawn & garden)
		10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes. No. If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No

5] TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued. <u>X</u> Clamped.
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter: <u>5</u> in. to <u>26</u> ft., Dia. in. to ft., Dia. in. to ft.			Threaded.
Casing height above land surface: <u>12</u> in., weight <u>2.40</u> lbs./ft. Wall thickness or gauge No. <u>160psi</u>			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify) ft.
SCREEN-PERFORATED INTERVALS: From: <u>26</u> ft. to <u>36</u> ft., From: ft. to ft., From: ft. to ft.			
GRAVEL PACK INTERVALS: From: <u>17</u> ft. to <u>36</u> ft., From: ft. to ft., From: ft. to ft.			

6] GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From: <u>3</u> ft. to <u>17</u> ft., From: ft. to ft., From: ft. to ft.				
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
Direction from well? <u>200</u>				13 Insecticide storage
				14 Abandoned water well
				15 Oil well/Gas well
				16 Other (specify below)
				How many feet? <u>South</u>

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	18	clay			
18	21	sand			
21	27	clay			
27	35	sand			
35	36	shale			

7] CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>1-8-02</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. <u>318</u> This Water Well Record was completed on (mo/day/yr) <u>1-8-02</u> under the business name of <u>Weninger Drilling Inc.</u> by (signature) <u>Richard Georges</u>
--