

1	LOCATION OF WATER WELL: Harvey	FRACTION NE 1/4 NE 1/4 NW 1/4	SECTION NUMBER 27	TOWNSHIP NUMBER T 24 S	RANGE NUMBER R 1W E/W
---	--	---	-----------------------------	----------------------------------	---------------------------------

Distance and direction from nearest town or city street address of well if located within city?

1/2 mile East of Ridge Sedgwick, Kansas

2	WATER WELL OWNER:	FIELDS, Scott	
	RR#, ST. ADDRESS, BOX #:	5619 S.W. 84th	Board of Agriculture, Division of Water Resource
	CITY, STATE:	Sedgwick, Kansas	Application Number:
		ZIP CODE:	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N	
NW	NE
SW	SE
S	

1 Mile

4 DEPTH OF COMPLETED WELL: **70** ft. ELEVATION:

Depth of groundwater Encountered: ft.

WELL'S STATIC WATER LEVEL **25** FT. BELOW LAND SURFACE MEASURED ON **10/22/03** mo/day/yr:

Pump test data: Well water was ft. after hours of pumping @ gpm

Est. Yield: gpm Well water was ft. after hours of pumping @ gpm

Bore Hole Diameter **12** in. to **70** ft. and in. to ft.

WELL WATER TO BE USED AS:

1. Domestic 3. Feedlot 5. Public water supply **7. Lawn and garden only** 9. Dewatering 11. Injection well

2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well 12. Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? YES **NO** ; if yes, what mo/day/yr was sample submitted

Was Water Well Disinfected? **YES** NO

5		TYPE OF CASING USED:		7. Fiberglass		9. Other (Specify below)		CASING JOINTS:		10. Threaded	
1. Steel		3. RPM (SR)		7. Wrought Iron		9. SDR-26		Glued		Clamped	
2. PVC		4. ABS		8. Concrete tile				Welded			
Blank casing diameter		5 in.		to 40 ft., Dia.		in. to ft., Dia.		in. to ft.			
Casing height above land surface:		12 in.,		Weight:		2.35 lbs. / ft.		Wall thickness or gauge No.		.214	
TYPE OF SCREEN OR PERFORATION MATERIAL:											
1. Steel		3. Stainless Steel		5. Fiberglass		7. PVC		9. ABS		11. Other (specify)	
2. Brass		4. Galvanized		6. Concrete Tile		8. RMP (SR)		10. Asbestos-Cement		12. None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:											
1. Continuous slot		3. Mill slot		5. Gauzed wrapped		7. Torch cut		9. Drilled holes		11. None (open hole)	
2. Louvered shutter		4. Key punched		6. Wire wrapped		8. Saw cut		10. Other (specify)			
SCREEN - PERFORATION INTERVAL		From		40 ft.		to 70 ft.,		From ft.		to ft.	
		From		ft.		to ft.,		From ft.		to ft.	
GRAVEL PACK INTERVALS:		From		24 ft.		to 70 ft.,		From ft.		to ft.	
		From		ft.		to ft.,		From ft.		to ft.	

6	GROUT MATERIALS:										
	1. Neat cement		2. Cement Grout		3. Bentonite		Other bentonite hole plug				
	Grout Intervals:	From 4 ft.	to 24 ft.,	From	ft.	to	ft.,	From	ft.	to	ft.
	What is the nearest source of possible contamination:										
	1. Septic tank	4. Lateral lines	7. Pit privy	10. Livestock pens	13. Insecticide storage	15. Oil well/Gas well					
	2. Sewer lines	5. Cess Pool	8. Sewage lagoon	11. Fuel storage	14. Abandon water well	16. Other (specify below)					
	3. Watertight sewer line	6. Seepage pit	9. Feed yard	12. Fertilizer storage							
	Direction from well? Southeast				How many feet? 130						

[illegible]

7. Contractor's or Landowner's Certification: This water well was 1. **constructed** 2. **reconstructed** or 3. **plugged** under my jurisdiction and was completed on (mo/day/year) **10/22/2003** and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. **236** This water well record was completed on (mo/day/year) **10/24/2003**

under the business name of **Harp Well & Pump Service Inc.** by (signature) *To d d S. Harp*