

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Harvey</u>	<u>SE 1/4 NE 1/4 SE 1/4</u>	<u>30</u>	T <u>24</u> S	R <u>1</u> EW

Distance and direction from nearest town or city street address of well if located within city?

From Sedgwick, KS: 2 miles West and 1 1/4 miles North2 WATER WELL OWNER: Wilbur and Lois Kury TrustRR#, St. Address, Box #: 9025 S. Mission Rd.City, State, ZIP Code: Sedgwick, KS 67135

Board of Agriculture, Division of Water Resources

Application Number: 125333 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL: 155 ft. ELEVATION:Depth(s) Groundwater Encountered 1 25 ft. 2 ft. 3 ft.WELL'S STATIC WATER LEVEL 26 ft. below land surface measured on mo/day/yr 7-9-04

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield 1200 gpm: Well water was ft. after hours pumping gpm

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

☒ Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring wellWas a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submittedWater Well Disinfected? Yes X No5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped

1 Steel 3 RMP (SR)

☒ PVC 16 ABS

6 Asbestos-Cement

7 Fiberglass

9 Other (specify below)

Welded

Threaded

Blank casing diameter 16 in. to 75 ft., Dia 16 in. to 95-115 ft., DiaCasing height above land surface 12 in., weight 16 lbs./ft. Wall thickness or gauge No. 1/2"

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel 3 Stainless Steel

5 Fiberglass

☒ PVC

10 Asbestos-Cement

2 Brass 4 Galvanized Steel

6 Concrete tile

8 RMP (SR)

11 Other (Specify)

12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot ☒ Mill slot

5 Gauzed wrapped

8 Saw cut

11 None (open hole)

2 Louvered shutter

4 Key punched

6 Wire wrapped

9 Drilled holes

7 Torch cut

10 Other (specify) ft.

SCREEN-PERFORATED INTERVALS: From 75 ft. to 95 ft., From 115 ft. to 155 ft.

From ft. to ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 20 ft. to 155 ft., From ft. to ft.

From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 3 ft. to 20 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank

4 Lateral lines

7 Pit privy

10 Livestock pens

☒ Abandoned water well

2 Sewer lines

5 Cess pool

8 Sewage lagoon

11 Fuel storage

15 Oil well/Gas well

3 Watertight sewer lines

6 Seepage pit

9 Feedyard

12 Fertilizer storage

16 Other (specify below)

13 Insecticide storage

Direction from well? SWHow many feet? 30

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Topsoil			
3	10	Sandy Soil			
10	35	Clay			
35	55	Small Gravel			
55	65	Med. Gravel			
65	85	Coarse Sand to Small Gravel			
85	108	Coarse Sand to Small Gravel			
		w/ clay streaks			
108	125	Reddish Clay			
125	155	Small Gravel w/ clay streaks			
155		Shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ constructed, (2) reconstructed, or (3) plugged under my jurisdiction and wascompleted on (mo/day/year) 7-8-04 and this record is true to the best of my knowledge and belief. KansasWater Well Contractor's Licence No 238 This Water Well Record was completed on (mo/day/yr) 7-10-04under the business name of Wenger Irrigation by (signature) Wenger