WATER WELL RECOR	D Form WWC-5	KSA 82a-1212	
1 LOCATION OF WATER WELL: FRACTION	SECTION NUMBER		RANGE NUMBER
Harvey SW 1/4 NW 1/4 Distance and direction from nearest town or city street address of well if located within city	SW 1/4 35	T 24 S	R 1W E/W
Ridge Rd. & 125th N., 1 mile E., 3/8 mile N. to Douglas Sedgwick, Kansas			
2 WATER WELL OWNER: OLSON, Kirk			
RR#,ST. ADDRESS,BOX #: 1011 Douglas		Board of Ag	riculture, Division of Water Resource
CITY, STATE: Sedgwick, Kansas	ZIP CODE:	Application Nu	mber:
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	100 ft.	ELEVATION:	
N Depth of groundwater Encountered:	ft.	ft.	ft.
WELL'S STATIC WATER LEVEL		SURFACE MEASURED ON mo.	• •
	Well water was		s of pumping @ gpm
Est. Yield: gpm E Bore Hole Diameter 12 in.	Well water was to 100	ft. after hour ft. and in.	rs of pumping @ gpm to ft.
₩ELL WATER TO BE USED AS:		O Dewater	44 1 1 1 1 1 1
1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 12. Other (Specify below)			
2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well Was a chemical/bacteriological sample submitted to Department? YFS NO ; If yes, what mo/day/yr was sample			
S Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample submitted Was Water Well Disinfected? YES NO			
5 TYPE OF CASING USED: 5. Wrought Iron 7. Fil	berglass 9. Other (Spec	cify below) CASING JOINTS:	Glued Threaded
1. Steel 3. RPM (SR)	oncrete tile SDR-26		Welded Clamped
4. Ab3		ft., Dia.	in. to ft.
10			
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No214 TYPE OF SCREEN OR PERFORATION MATERIAL:			
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)			
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:			
1. Continuous slot 3. Mill slot 5. Gauzed wrapped	7. Torch cut	9. Drilled holes	11. None (open hole)
2. Louvered shutter 4. Key punched 6. Wire wrapped	8. Saw cut	10. Other (specify)	
SCREEN - PERFORATION INTERVAL From 25 ft.	to 100 ft.,	From ft.	to ft.
From ft.	to ft.,	From ft.	to ft.
GRAVEL PACK INTERVALS: From 24 ft.	to 100 ft.,	From ft.	to ft.
From ft.	to ft.,	From ft.	to ft.
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug			
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination:			
1. Septic tank 4. Lateral lines 7. Pit privy	10. Livestock pens	13. Insecticide storage	15. Oil well/Gas well
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)			
3 Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage None Apparent			
Direction from well? North	Fram To	How many feet? 40	
From To LITHOLOGIC LOG 0 3 topsoil	From To	LITHOLI	OGIC LOG
3 10 clay			
10 15 fine sand			
15 17 sandy clay 17 100 shale			
17 100 shale			
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2, reconstructed or 3, plugged under my jurisdiction and			
was completed on (mo/day/year) 1/8/2004 and this record is true to the best of my knowledge and belief.			
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 1/12/2004			
under the business name of Harp Well & Pump Service Inc. by (signature) Jo d d S. Harp			