

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: <u>Reno</u>		<u>NE 1/4 NE 1/4 NE 1/4</u>		<u>36</u>		T <u>24</u> S		R <u>10</u> E/W	
Distance and direction from nearest town or city street address of well if located within city?									
2 WATER WELL OWNER: <u>Lee Wenger</u>									
RR#, St. Address, Box # : <u>11107 So. Jordan Spgs. Rd</u>						Board of Agriculture, Division of Water Resources			
City, State, ZIP Code : <u>Sylvia, KS. 62581</u>						Application Number:			
3 LOCATE WELL'S LOCATION WITH		4 DEPTH OF COMPLETED WELL <u>60</u> ft. ELEVATION:							
AN "X" IN SECTION BOX:		Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft.							
<div><div><div>N</div><div>W</div><div>E</div><div>S</div></div><div><div>NW</div><div>NE</div><div>SE</div><div>SW</div></div></div>		WELL'S STATIC WATER LEVEL <u>42</u> ft. below land surface measured on mo/day/yr <u>9-13-04</u>							
		Pump test data: Well water was ft. after hours pumping gpm							
		Est. Yield gpm: Well water was ft. after hours pumping gpm							
		WELL WATER TO BE USED AS:							
		1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well							
		2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below)							
		7 Domestic (lawn & garden) 10 Monitoring well							
		Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was submitted							
		Water Well Disinfected? Yes <u>X</u> No							
5 TYPE OF BLANK CASING USED:									
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: <u>Glued</u> Clamped									
2 <u>PVC</u> 4 ABS 7 Fiberglass 9 Other (specify below) <u>Welded</u> Threaded									
Blank casing diameter <u>5</u> in. to <u>40</u> ft., Dia in. to ft., Dia in. to ft.									
Casing height above land surface <u>20</u> in., weight <u>160#</u> lbs./ft. Wall thickness or guage No. <u>214</u>									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1 Steel 3 Stainless Steel 5 Fiberglass 7 <u>PVC</u> 10 Asbestos-Cement									
2 Brass 4 Galvanized Steel 6 Concrete tile 8 RMP (SR) 11 Other (Specify)									
9 ABS 12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
1 Continuous slot 3 Mill slot 5 Guazed wrapped 8 <u>Saw cut</u> 11 None (open hole)									
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes									
7 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS: From <u>40</u> ft. to <u>60</u> ft., From ft. to ft.									
GRAVEL PACK INTERVALS: From <u>60</u> ft. to <u>20</u> ft., From ft. to ft.									
FROM ft. to ft., From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other <u>Hole Plug</u>									
Grout Intervals: From <u>20</u> ft. to <u>3</u> ft., From ft. to ft.									
What is the nearest source of possible contamination:									
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well									
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well									
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)									
13 Insecticide storage									
Direction from well? <u>South</u> How many feet? <u>25</u>									
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS									
<u>0 4 Sandy Top Soil</u>									
<u>4 10 Tan Clay. Sandy 50/50</u>									
<u>10 20 Tan Clay</u>									
<u>20 25 Tan Clay</u>									
<u>25 60 Fine to Medium Sand</u>									
RECEIVED									
OCT 13 2004									
BUREAU OF WATER									