

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Reno		SW ¼ NW ¼ SE ¼		15		T 24 S		R 10 E/W	
Distance and direction from nearest town or city street address of well if located within city? 118 Main, Sylvia, Kansas									
2 WATER WELL OWNER: Sylvia Coop									
RR#, St. Address, Box # : 118 N. Main					Board of Agriculture, Division of Water Resources				
City, State, ZIP Code : Sylvia, KS 67581					Application Number:				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:			4 DEPTH OF COMPLETED WELL: 15 ft. ELEVATION: 0						
			Depth(s) Groundwater Encountered 1. 12 ft. 2. ft. 3. ft.						
			WELL'S STATIC WATER LEVEL: ft. below land surface measured on mo/day/yr						
			Pump test data: Well water was NA ft. after hours pumping gpm						
			Est. Yield NA gpm: Well water was ft. after hours pumping gpm						
			Bore Hole Diameter 11 in. to 15 ft. and in. to ft.						
			WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well						
			1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)						
			2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring Vapor extraction we.						
			Was a chemical/bacteriological sample submitted to Department? Yes No ☒ If yes, mo/day/yr sample was submitted						
			Water Well Disinfected? Yes No ☒						
5 TYPE OF BLANK CASING USED:									
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped									
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded									
Blank casing diameter 4 in. to 5 ft. Dia. in. to ft. Dia. in. to ft.									
Casing height above land surface in., weight lbs./ft. Wall thickness or gauge No. Sch. 40									
TYPE OF SCREEN OR PERFORATION MATERIAL									
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement									
2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)									
SCREEN OR PERFORATION OPENINGS ARE:									
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)									
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes									
7 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS: From 5 ft. to 15 ft. From ft. to ft.									
GRAVEL PACK INTERVALS: From 4 ft. to 15 ft. From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other									
Grout Intervals: From 2 ft. to 4 ft. From ft. to ft. From ft. to ft.									
What is the nearest source of possible contamination:									
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well									
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well									
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)									
Direction from well? West 13 Insecticide storage Dispenser island.									
How many feet? 50									
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS									
0 6 Clay, silty, sl. sandy, sl. plastic, sl. moist, Dark									
6 10 Clay, silty, sandy, sl. plastic, sl. moist, Grayish									
10 12 Sand (f-c), sl. silty, sl. moist, Brown									
12 15 Sand (f-c), sl. silty, saturated, sl. odor, Gray/B									
RECEIVED									
NOV 22 2004									
BUREAU OF WATER									
VIEW3R, Tag # 00333748									
Project Name: GF - Sylvia Coop									
GeoCore # 897, KDHE # A2 078 40106									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8/5/2004 and this record is true to the best of my knowledge and belief.									
Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 7/1/04									
under the business name of GeoCore, Inc. by (signature) Dale Hobbs									