

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number																																				
County: Reno		SW ¼ NW ¼ SE ¼	15	T 24 S	R 10 E W																																				
Distance and direction from nearest town or city street address of well if located within city? 118 Main, Sylvia, Kansas																																									
2 WATER WELL OWNER: Sylvia Coop RR#, St. Address, Box # : 118 N. Main City, State, ZIP Code : Sylvia, KS 67581 Board of Agriculture, Division of Water Resources Application Number:																																									
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 26 ft ELEVATION: 0																																							
		Depth(s) Groundwater Encountered 1. 11 ft 2. 11 ft 3. 11 ft WELL'S STATIC WATER LEVEL 10 ft below land surface measured on mo/day/yr 8/6/2004 Pump test data: Well water was NA ft. after NA hours pumping NA gpm Est. Yield NA gpm: Well water was NA ft. after NA hours pumping NA gpm Bore Hole Diameter 8 in. to 26 ft, and NA in. to NA ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes NA No ☒ If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes NA No ☒																																							
		5 TYPE OF BLANK CASING USED:																																							
		1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued NA Clamped NA 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded NA Blank casing diameter 2 in. to 24 ft, Dia. NA in. to NA ft, Dia. NA in. to NA ft. Casing height above land surface NA in., weight NA lbs./ft. Wall thickness or gauge No. Sch. 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) NA 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) NA SCREEN-PERFORATED INTERVALS: From 24 ft to 26 ft, From NA ft to NA ft From NA ft to NA ft, From NA ft to NA ft GRAVEL PACK INTERVALS: From 22 ft to 26 ft, From NA ft to NA ft From NA ft to NA ft, From NA ft to NA ft																																							
		6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other NA																																							
Grout Intervals: From 2 ft to 22 ft, From NA ft to NA ft, From NA ft to NA ft What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Contaminated site 13 Insecticide storage Direction from well? 0 How many feet? 0																																									
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>FROM</th> <th>TO</th> <th>LITHOLOGIC LOG</th> <th>FROM</th> <th>TO</th> <th>PLUGGING INTERVALS</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>3.5</td> <td>Clay, v. silty, v. sandy, sl. plastic, sl. moist, Dar</td> <td></td> <td></td> <td></td> </tr> <tr> <td>3.5</td> <td>15</td> <td>Sand, silty, clayey, sl. moist (backfill), Brown/</td> <td></td> <td></td> <td></td> </tr> <tr> <td>15</td> <td>17</td> <td>Clay, v. silty, v. sandy, saturated, Brown</td> <td></td> <td></td> <td></td> </tr> <tr> <td>17</td> <td>21</td> <td>Clay, v. silty, v. sandy, saturated, Gray</td> <td></td> <td></td> <td></td> </tr> <tr> <td>21</td> <td>26</td> <td>Sand (f-c), silty, saturated, Gray/Brown</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>						FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	0	3.5	Clay, v. silty, v. sandy, sl. plastic, sl. moist, Dar				3.5	15	Sand, silty, clayey, sl. moist (backfill), Brown/				15	17	Clay, v. silty, v. sandy, saturated, Brown				17	21	Clay, v. silty, v. sandy, saturated, Gray				21	26	Sand (f-c), silty, saturated, Gray/Brown			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS																																				
0	3.5	Clay, v. silty, v. sandy, sl. plastic, sl. moist, Dar																																							
3.5	15	Sand, silty, clayey, sl. moist (backfill), Brown/																																							
15	17	Clay, v. silty, v. sandy, saturated, Brown																																							
17	21	Clay, v. silty, v. sandy, saturated, Gray																																							
21	26	Sand (f-c), silty, saturated, Gray/Brown																																							
RECEIVED NOV 22 2004 BUREAU OF WATER																																									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8/4/2004 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 7/1/04 under the business name of GeoCore, Inc. by (signature) <i>Dan Vell</i>																																									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.																																									

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4