

LOCATION OF WATER WELL: County: Reno		Fraction SW₄ SW ¹/₄ SE₁/₄	Section Number 15	Township Number T 24 S	Range Number R 10 E
Distance and direction from nearest town or city street address of well if located within city? Trails West Road, Sylvia, Ks.					
WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :		George Martin Trust P.O. Box 7 Sylvia, Ks. Board of Agriculture, Division of Water Resources Application Number:			
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: N +--- NW ---+ NE ---+ +--- SW ---+ SE ---+ S X is in SW corner		DEPTH OF COMPLETED WELL 17 ft. ELEVATION: NA Depth(s) Groundwater Encountered 1. 10 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 9.65 ft. below land surface measured on mo/day/yr 12-28-93 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 7.5/8 in. to 17 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only (10) Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes.....No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X			
TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) (2) PVC 4 ABS Blank casing diameter 2 in. to 7 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 0 in., weight lbs./ft. Wall thickness or gauge No. sch. 40		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded X			
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot (3) Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 3 Torch cut 10 Other (specify)		12 Asbestos-cement 11 Other (specify) 12 None used (open hole)			
SCREEN-PERFORATED INTERVALS: From 7 ft. to 17 ft., From ft. to ft. From ft. to ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 6 ft. to 17 ft., From ft. to ft. From ft. to ft., From ft. to ft.					
GROUT MATERIAL: 1 Neat cement (2) Cement grout (3) Bentonite 4 Other Grout Intervals: From 0 ft. to 4 ft., From 4 ft. to 6 ft., From ft. to ft.		What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy (1) Fuel storage 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage 16 Other (specify below) Direction from well? north How many feet? 50			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	5	cly, v dk brn, mod-v sndy, moist			
5	9	snd, mod gy/gn, f-c, sl slty, p srt'd, damp			
9	17	snd, lt gn-lt brn, f-c w/f-m grvl, p srt'd, damp			
					MW2-flush mount cover Site ID # 00066505
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 01-03-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 02-09-94 under the business name of GedCore Services, Inc. by (signature) <i>Dale G. [Signature]</i>					