

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Reno		SW SW ¼ SE ¼	15	T 24 S	R 10 E
Distance and direction from nearest town or city street address of well if located within city?					
Trails West Road, Sylvia, Ks.					
2 WATER WELL OWNER:		George Martin Trust			
RR#, St. Address, Box # :		P.O. Box 7			
City, State, ZIP Code :		Sylvia, Ks.			
		Board of Agriculture, Division of Water Resources Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 18 ft. ELEVATION: NA			
1 Mile scale bar		Depth(s) Groundwater Encountered 1. 11 ft. 2. .ft. 3. .ft.			
		WELL'S STATIC WATER LEVEL 10.10 ft. below land surface measured on mo/day/yr 12-28-93			
		Pump test data: Well water was .ft. after . hours pumping gpm			
		Est. Yield gpm: Well water was .ft. after . hours pumping gpm			
		Bore Hole Diameter 7 5/8 in. to 18 ft., and .in. to .ft.			
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes.....No.. X; If yes, mo/day/yr sample was submitted		Water Well Disinfected? Yes No X			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued . Clamped .			
1 Steel 3 RMP (SR) 2 PVC 4 ABS Blank casing diameter . 2 .in. to 8 .ft., Dia .in. to .ft., Dia .in. to .ft. Casing height above land surface . 0 .in., weight . lbs./ft. Wall thickness or gauge No. sch. 40		5 Wrought iron 8 Concrete tile 6 Asbestos-Cement 9 Other (specify below) 7 Fiberglass Threaded. X			
TYPE OF SCREEN OR PERFORATION MATERIAL:		1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)			
SCREEN-PERFORATED INTERVALS:		From . 7 .ft. to 17 .ft., From .ft. to .ft.			
GRAVEL PACK INTERVALS:		From . 6 .ft. to 17 .ft., From .ft. to .ft.			
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From . 0 .ft. to 5 .ft., From . 5 .ft. to 7 .ft., From .ft. to .ft.			
What is the nearest source of possible contamination:		1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage 16 Other (specify below)			
Direction from well? northwest		How many feet? 290			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	clay, dk brn, v slty, damp			
2	5	clay, v lt brn, mod slty, tr snd, tr caliche, damp			
5	7	clay, lt gy/gn, v sandy, moist			
7	9	sand, lt gn/brn, vf-f, tr clay, mod srted, moist			
9	18	sand, lt brn, f-v c, w/mod f-m grvl, p srted, moist-sat			
MW9-flush mount cover Site ID # 00066741					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 01-06-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 02-09-94 under the business name of GeoCore Services, Inc. by (signature) <i>[Signature]</i>					