

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Stafford</u>	<u>NE ¼ SW ¼ NE ¼</u>	<u>6</u>	<u>T 24 S</u>	<u>R 12 E/W</u>

Distance and direction from nearest town or city street address of well if located within city?

3 3/4 East of St. John

2 WATER WELL OWNER: XXXXXXXXXX <u>Turner Farms</u>	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # : <u>P.O. Box 460</u>	Application Number: <u>24710</u>
City, State, ZIP Code : <u>Great Bend, Ks. 67530</u>	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL <u>116</u> ft. ELEVATION:
	Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL <u>27</u> ft. below land surface measured on mo/day/yr <u>1-14-06</u> Pump test data: Well water was <u>59' 4"</u> ft. after <u>4 1/2</u> hours pumping <u>977</u> gpm Est. Yield <u>1195</u> gpm: Well water was <u>62' 4"</u> ft. after <u>5</u> hours pumping <u>1195</u> gpm WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 <u>Irrigation</u> 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well
	Was a chemical/bacteriological sample submitted to Department? Yes 3 No <u>X</u> ; If yes, mo/day/yr sample was submitted <u>1-17-06</u> Water Well Disinfected? Yes <u>HTH</u> No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped
1 Steel	6 Asbestos-Cement	9 Other (specify below)	Welded
2 <u>PVC</u>	7 Fiberglass		Threaded
3 RMP (SR)			
4 ABS			
Blank casing diameter <u>16</u> in. to <u>56</u> ft., Dia			
Casing height above land surface <u>24</u> in., weight <u>Sch 40</u> lbs./ft. Wall thickness or gauge No.			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 <u>PVC</u>	10 Asbestos-Cement	
1 Steel	8 RMP (SR)	11 Other (Specify)	
2 Brass	9 ABS	12 None used (open hole)	
3 Stainless Steel			
4 Galvanized Steel			
5 Fiberglass			
6 Concrete tile			
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 <u>Continuous slot</u>	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	7 Torch cut	10 Other (specify)	
3 Mill slot			
4 Key punched			
SCREEN-PERFORATED INTERVALS:	From <u>116</u> ft. to <u>56</u> ft., From		
	From ft. to ft., From		
GRAVEL PACK INTERVALS:	From <u>116</u> ft. to <u>20</u> ft., From		
	From ft. to ft., From		

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other <u>hole plug</u>
Grout intervals: From <u>20</u> ft. to <u>0</u> ft., From				
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	<u>None</u>
Direction from well?			How many feet?	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	7	Fine sand			
7	18	Sandy clay			
18	21	Clay			
21	42	Med Med sand & gravel			
42	50	Clay			
50	55	Sand, gravel, & clay mixed			
55	60	Small sand & gravel			
60	70 1/2	Clay			
70 1/2	74	Sand, gravel, & clay mixed			
74	79	Clay			
79	94	Sand & gravel			
94	96	Clay			
96	108	Sand & XXXX gravel			
108	116	Clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>1-19-06</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No <u>134</u> This Water Well Record was completed on (mo/day/yr) <u>2-13-06</u> under the business name of <u>Rosencrantz- Bemis</u> by (signature) <u>Tara Albee</u>
