

WESLEY #1

WATER WELL RECORD

Form WWC-5

KSA 82a-1212

1

LOCATION OF WATER WELL:

Fraction

Section Number

Township Number

Range Number

County: STAFFORD

SW 1/4 NE 1/4 SE 1/4

18

T 24 S

R 12 E

Distance and direction from nearest town or city street address of well if located within city?

STAFFORD 3 1/2 W 3/4 S WESTSIDE.

2

WATER WELL OWNER:

RR#, St. Address, Box #

City, State, ZIP Code

J.W. DRILLING CO. INC.

200 E. FIRST SUITE 500

WICHITA, KS 67202

M. WESLEY, STAFFORD, KS.

Board of Agriculture, Division of Water Resources

Application Number: T84-181

3

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

N

W

E

S

NW

NE

SW

SE

4

DEPTH OF COMPLETED WELL

ft.

ELEVATION:

75

26

40

Depth(s) Groundwater Encountered

1.

ft.

2.

ft.

3.

ft.

WELL'S STATIC WATER LEVEL

24

ft. below land surface measured on mo/day/yr

3-22-84

Pump test data:

Well water was

ft. after

hours pumping

gpm

Est. Yield

gpm

Well water was

ft. after

hours pumping

gpm

Bore Hole Diameter

7 1/8

in. to

75

ft., and

in. to

ft.

WELL WATER TO BE USED AS:

5 Public water supply

8 Air conditioning

11 Injection well

1 Domestic

3 Feedlot

6 Oil field water supply

9 Dewatering

12 Other (Specify below)

2 Irrigation

4 Industrial

7 Lawn and garden only

10 Observation well

Was a chemical/bacteriological sample submitted to Department? Yes

No

If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes

No

5

TYPE OF BLANK CASING USED:

1 Steel

3 RMP (SR)

2 PVC

4 ABS

5 Wrought iron

6 Asbestos-Cement

7 Fiberglass

8 Concrete tile

9 Other (specify below)

CASING JOINTS: Glued

Clamped

Welded

Threaded

Blank casing diameter

5

in. to

55

ft., Dia

in. to

ft.

Casing height above land surface

1.2

in., weight

2.65

lbs./ft. Wall thickness or gauge No.

214

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel

3 Stainless steel

5 Fiberglass

7 PVC

10 Asbestos-cement

2 Brass

4 Galvanized steel

6 Concrete tile

8 RMP (SR)

11 Other (specify)

12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot

3 Mill slot

5 Gauzed wrapped

8 Saw cut

11 None (open hole)

2 Louvered shutter

4 Key punched

6 Wire wrapped

9 Drilled holes

SCREEN-PERFORATED INTERVALS:

From

55

ft. to

75

ft., From

ft. to

ft.

GRAVEL PACK INTERVALS:

From

24

ft. to

75

ft., From

ft. to

ft.

6

GROUT MATERIAL:

1 Neat cement

2 Cement grout

3 Bentonite

4 Other

Grout Intervals: From

0

ft. to

1.0

ft., From

ft. to

ft.

What is the nearest source of possible contamination:

NONE

10 Livestock pens

14 Abandoned water well

1 Septic tank

4 Lateral lines

7 Pit privy

11 Fuel storage

15 Oil well/Gas well

2 Sewer lines

5 Cess pool

8 Sewage lagoon

12 Fertilizer storage

16 Other (specify below)

3 Watertight sewer lines

6 Seepage pit

9 Feedyard

13 Insecticide storage

Direction from well?

How many feet?

FROM

TO

LITHOLOGIC LOG

FROM

TO

LITHOLOGIC LOG

0

10

SANDY LOAM

10

20

CLAY

20

30

GRAVEL

30

40

SANDY CLAY

40

75

GRAVEL

7

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION:

This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)

3-22-84

and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No.

389

This Water Well Record was completed on (mo/day/yr)

3-28-84

under the business name of

REISER WATERWELL SERV. INC.

by (signature)

Rudolph Reiser

INSTRUCTIONS:

Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4