


1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Stafford	SW 1/4 SW 1/4 NW 1/4	2	T 24 S	R 13 EW

Distance and direction from nearest town or city street address of well if located within city?

Stafford County Landfill

2 WATER WELL OWNER:	Stafford County	01968014	MW-4
RR#, St. Address, Box #	209 North Broadway	Board of Agriculture, Division of Water Resources	
City, State, ZIP Code	St. John, Kansas 67576	Application Number:	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 43 ft. ELEVATION: Aprox Surface 1905
	Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL 31 ft. below land surface measured on mo/day/yr 05/23/96
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield N/A gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter 8.25 in. to 43 ft., and in. to ft.
	WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
	Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was sub-
	mitted Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped	
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)	Welded
2 PVC	4 ABS	7 Fiberglass		Threaded. X
Blank casing diameter 0 in. to 33 ft., Dia in. to ft., Dia in. to ft.				
Casing height above land surface 36 in., weight lbs./ft. Wall thickness or gauge No. Schedule 40				
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement		
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)	
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes	
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From 33 ft. to 43 ft., From ft. to ft.				
GRAVEL PACK INTERVALS: From 31 ft. to 43 ft., From ft. to ft.				

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other	
Grout Intervals: From 0 ft. to 29 ft., From 29 ft. to 31 ft., From ft. to ft.					
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well?				13 Insecticide storage	
				How many feet?	

FROM		TO		LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1.5	1.5	6.0	Fine to Medium Sand, Light Brown			
1.5	6.0	6.0	8.0	Fine Sand, Light Brown to Brown			
6.0	8.0	8.0	11.0	Fine Sand, Brown			
8.0	11.0	11.0	18.0	Fine to Medium Sand, Red-Brown, With Thin Fat Clay Seams			
11.0	18.0	18.0	24.0	Fine to Medium Sand, Red-Brown			
18.0	24.0	24.0	31.0	Fine to Medium Sand, Orange-Brown			
24.0	31.0	31.0	41.0	Fine Sand, Gray-Brown			
31.0	41.0	41.0	43.0	Fine Sand, Brown to Orange-Brown			
41.0	43.0	43.0		Lean to Fat Clay, Brown			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 05/22/96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 05/22/96 under the business name of Terracon Consultants, Inc. by (signature) <i>Steve Fisher</i>
