

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Stafford</u>		<u>NW 1/4 NW 1/4 NW 1/4</u>	<u>4</u>	T <u>24</u> S	R <u>13</u> E <u>(W)</u>
Distance and direction from nearest town or city street address of well if located within city? <u>Well is located on side</u>					
2 WATER WELL OWNER: <u>St. John Farmers Coop</u>					
RR#, St. Address, Box #: <u>312 West 1st.</u>					
City, State, ZIP Code: <u>St. John, KS</u>					
Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>20'</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered <u>1.16'</u> ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL <u>16.40'</u> ft. below land surface measured on mo/day/yr <u>6-30-97</u>			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm; Well water was ft. after hours pumping gpm			
		Bore Hole Diameter <u>3 1/2"</u> in. to <u>20'</u> ft. and in. to ft.			
WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Dewatering 12 Other (Specify below) <u>SVE well</u> Was a chemical/bacteriological sample submitted to Department? Yes <u>(No)</u> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u>(No)</u>					
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 <u>PVC</u> 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded <u>X</u>					
Blank casing diameter <u>2.375</u> in. to <u>10'</u> ft. Dia. in. to ft. Dia. in. to ft.					
Casing height above land surface <u>Flush Mt.</u> in., weight lbs./ft. Wall thickness or gauge No. <u>SD-13</u>					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From <u>20'</u> ft. to <u>10'</u> ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From <u>20'</u> ft. to <u>8'</u> ft. From ft. to ft.					
6 GROUT MATERIAL:					
1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From <u>8'</u> ft. to <u>6'</u> ft. From <u>6'</u> ft. to <u>4'</u> ft. From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage					
Direction from well? <u>West (75 ft)</u> How many feet? <u>75'</u>					
LITHOLOGIC LOG					
FROM	TO	LITHOLOGIC LOG		FROM	TO
0	1.0	Gravel road base, packed			
1.0	4.5	Black, sandy clay, dry, friable, mod odor			
4.5	6.5	Bn to Black sandy clay is clayey and fine grained, dry, mod odor			
6.5	11.5	Bn clayey and dry to damp, mod odor fine grained, well rounded			
11.5	15.5	Green fine-coarse sand & gravel, moist, mod odor, well rounded			
15.5	20.0	Black, fine-coarse grained sand & gravel wet to 16', strong odor, well rounded			
PLUGGING INTERVALS					
F.H. installed for Remediation Contr. Job.					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>6-30-97</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>539</u> This Water Well Record was completed on (mo/day/yr) <u>7-15-97</u> under the business name of <u>JB Environmental Drilling</u> by (signature) <u>James Becker</u>					

OFFICE USE ONLY
T
R
EWM
SEC
1/4
1/4