


AG-2

1 LOCATION OF WATER WELL: Fraction NW 1/4 NW 1/4 NW 1/4 Section Number 4 Township Number T 24 S Range Number R 13 E/W
 County: STAFFORD

Distance and direction from nearest town or city street address of well if located within city?
312 W. 1st St., St. John, Kansas

2 WATER WELL OWNER: ST. JOHN FARMERS COOP
 RR#, St. Address, Box #: P.O. BOX 248, ST. JOHN, KS. 66570
 City, State, ZIP Code: ST. JOHN, KS. 66570
 Board of Agriculture, Division of Water Resources
 Application Number: 1604 00

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL 30.0 ft. ELEVATION: 1604.00
 Depth(s) Groundwater Encountered 1 20.0 ft. 2 ft. 3 ft.
 WELL'S STATIC WATER LEVEL N/A ft. below land surface measured on mo/day/yr N/A
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield N/A gpm: Well water was ft. after hours pumping gpm
 WELL WATER TO BE USED AS:
 1 Domestic 2 Irrigation 3 Feedlot 4 Industrial 5 Public water supply 6 Oil field water supply 7 Domestic (lawn & garden) 8 Air conditioning 9 Dewatering 10 Monitoring well 11 Injection well 12 None used (open hole)
11 Injection well
12 Other (Specify below) AIR SPARGE
 Was a chemical/bacteriological sample submitted to Department? Yes No ✓; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:
 1 Steel 2 Brass 3 RMP (SR) 4 Galvanized Steel 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below)
3 PVC 4 ABS
 Blank casing diameter 2.375 in. to 2.5 ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface FLUSH MOUNT in., weight lbs./ft. Wall thickness or gauge No. SCH 40
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 2 Brass 3 Stainless Steel 4 Galvanized Steel 5 Fiberglass 6 Concrete tile 7 Guazed wrapped 8 Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole)
7 PVC 10 Asbestos-Cement 11 Other (Specify) 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Guazed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole)
3 Mill slot
 SCREEN-PERFORATED INTERVALS: From 30 ft. to 21 ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 30 ft. to 20 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 0 ft. to 3 ft., From 3 ft. to 20 ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage (FORMER) 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)
 Direction from well? SOUTH How many feet? 15

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	0.5	LS ALL-			
0.5	5	DK BRN-BLK SANDY CLAY, FIRM, MOIST SLTDRP			
5	8	BR SANDY CLAY FIRM, MOIST			
8	20	BR FINE-COARSE GRAINED SANDS, GRAVEL PEBBLES, DRY			
20	30	GY FINE-COARSE GRAINED SANDS, GRAVEL, WELL GRAINED, WET, MOIST SLTDRP			
FLUSH-MOUNT WELL COMPLETION WAIVER EXISTENT FOR SITE.					

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/26/02 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 662 This Water Well Record was completed on (mo/day/yr) 11/26/02 under the business name of QUAD STATE SERVICES, INC. by (signature) [Signature]