

MW-15

1 LOCATION OF WATER WELL: County: STAFFORD		Fraction: NW 1/4 NW 1/4 NW 1/4	Section Number: 4	Township Number: T 24 S	Range Number: R 13 E (W)
Distance and direction from nearest town or city, street address of well if located within city? 312 W. 1st St., ST. JOHN, KANSAS					
2 WATER WELL OWNER: ST. JOHN FARMERS COOP RR#, St. Address, Box #: P.O. BOX 248, ST. JOHN, KS. 66516 City, State, ZIP Code: ST. JOHN, KS. 66516 Board of Agriculture, Division of Water Resources Application Number: * 1604 00					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 30.0 ft. ELEVATION: 1604.00			
		Depth(s) Groundwater Encountered: 1 20.0 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL: 20.62 ft. below land surface measured on mo/day/yr 12/3/02 Pump test data: Well water was ft. after hours pumping gpm Est. Yield: N/A gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 7 Domestic (lawn & garden) 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No ☒ If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No			
		TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 6 PVC 4 ABS 7 Fiberglass 9 Other (specify below) Welded Blank casing diameter: 2.375 in. to 15 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface: FLUSH MOUNT in., weight lbs./ft. Wall thickness or gauge No. 3CH 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-Cement 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 11 Other (Specify) 12 None used (open hole)			
		SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 6 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) ft.			
SCREEN-PERFORATED INTERVALS: From 30 ft. to 15 ft., From ft. to ft.		From 30 ft. to 15 ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From 30 ft. to 13 ft., From ft. to ft.		From ft. to ft., From ft. to ft.			
6 GROUT MATERIAL: 1 Neat cement 3 Cement grout 6 Bentonite 4 Other Grout Intervals: From 0 ft. to 3 ft., From 3 ft. to 13 ft., From ft. to ft.					
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage (FORMER) 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? SOUTHWEST How many feet? 20					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	0.5	CONCRETE			
0.5	5	DK BN SANDY CLAY, FIRM, MOIST, FAINT USUR			
5	9.5	BN SANDY CLAY, FIRM, MOIST			
9.5	16.5	BN FINE-COARSE GRAINED SAND, GRAVEL, PEBBLES, SL MOIST, FAINT- SL USUR			
16.5	30	FX-LN FINE-COARSE GRAINED SAND, GRAVEL, WET @ 20', MOD-ST USUR			
FLUSH MOUNT WELL COMPLETION WAIVER EXISTENT FOR SITE.					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/24/02 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 662 This Water Well Record was completed on (mo/day/yr) 11/24/02 under the business name of QUAK STATE SERVICES, INC. by (signature) [Signature]					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.					