

WATER WELL RECORD

Form WWC-5

Division of Water Resources: App. No.

Table with 4 columns: LOCATION OF WATER WELL, Fraction, Section Number, Township Number, Range Number. Values include Stafford, NW, SE, NW, 4, T 24 S, R 13 W.

Distance and direction from nearest town or city street address of well if located within city? 424 South Broadway, St. John Global Positioning System (decimal degrees, min. of 4 digits) Latitude: N 37.99436° Longitude: W 98.76073° Elevation: RIM: 1907.75 TOC: 1906.94 Datum: above mean sea level Data Collection Method: legal survey

2 WATER WELL OWNER: City of St. John RR#. St. Address, Box #: PO Box 367 City, State, ZIP Code: St. John, KS. 67576

3 LOCATE WELL'S SECTION WITH AN "X" IN SECTION BOX: [Diagram showing a 3x3 grid with NW, NE, SW, SE quadrants and an 'X' in the NW quadrant.] 4 DEPTH OF COMPLETED WELL 36 ft. AS16 Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 15.99 ft. below land surface measured on mo/day/yr 7/7/09 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feed lot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well Air Sparge Was a chemical/bacteriological sample submitted to Department? Yes No X : If yes, mo/day/yr Sample was submitted Water Well Disinfected? Yes No X

5 TYPE OF CASING USED: 1 Steel 2 PVC 3 RMP (SR) 4 ABS 5 Wrought Iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) CASING JOINTS: Glued Clamped Welded Threaded X Blank casing diameter 2 in. to 36 ft., Dia in. to ft., Dia in. to ft. Casing height below land surface 0.81 ft., Weight lbs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RM (SR) 9 ABS 10 Asbestos-Cement 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Gauze wrapped 6 Wire wrapped 7 Torch cut 8 Saw Cut 9 Drilled holes 10 Other (specify) 11 None (open hole) SCREEN-PERFORATED INTERVALS: From 33 ft. to 35 ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 30.25 ft. to 37 ft. From ft. to ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Coated Bentonite 3 Med. Bentonite 4 Other Concrete: 0-1.5 ft.; Soil: 1.5-4 ft. Grout Intervals From 4 ft. to 16.5 ft. From 16.5 ft. to 30.25 ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide Storage 14 Abandoned water well 15 Oil well/ gas well 16 Other (specify below) Direction from well? SW How many feet? ~260

Table with 6 columns: FROM, TO, LITHOLOGIC LOG, FROM, TO, LITHOLOGIC LOG. Rows describe geological layers from 0 to 25.5 feet depth, including gravel, silty clay, and sand.

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6/2/09 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 757. This Water Well Record was completed on (mo/day/year) 8/27/09 under the business name of Larsen & Associates, Inc. by (signature)

INSTRUCTIONS: Please fill in blanks or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell.