

1 LOCATION OF WATER WELL: County: STAFFORD, Fraction: SE 1/4 NE 1/4 NE 1/4, Section Number: 21, Township Number: T 24 S, Range Number: R 13 E. Distance and direction from nearest town or city street address of well if located within city? ST. JOHN 2 3/4 S WESTSIDE.

2 WATER WELL OWNER: WEST TRAIL EXPLORATION, RR#, St. Address, Box #: 1531 STROUT ST. SUITE 530, City, State, ZIP Code: DENVER, COLORADO 80202. Application Number: T84-411.

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 36-section grid with 'X' in the NE section of the top-left 4-section block.]

4 DEPTH OF COMPLETED WELL: 60 ft. ELEVATION: 7118 ft. WELL'S STATIC WATER LEVEL: 15 ft. below land surface measured on mo/day/yr 7-11-84. Pump test data: Well water was 18 ft. after 1 hour pumping 15 gpm. Est. Yield: 15 gpm. Well water was 60 ft. after 1 hour pumping 15 gpm. Bore Hole Diameter: 7.75 in. to 60 ft., and 60 in. to 15 ft. WELL WATER TO BE USED AS: 5 Public water supply, 8 Air conditioning, 11 Injection well, 1 Domestic, 3 Feedlot, 6 Oil field water supply, 9 Dewatering, 12 Other (Specify below), 2 Irrigation, 4 Industrial, 7 Lawn and garden only, 10 Observation well. Was a chemical/bacteriological sample submitted to Department? Yes. No. If yes, mo/day/yr sample was submitted. Water Well Disinfected? Yes. No.

5 TYPE OF BLANK CASING USED: 1 Steel, 3 RMP (SR), 6 Asbestos-Cement, 9 Other (specify below), 2 PVC, 4 ABS, 7 Fiberglass, 8 Concrete tile, CASING JOINTS: Glued, X, Clamped, Welded, Threaded. Blank casing diameter: 5 in. to 40 ft., Dia. 40 in. to 12 ft., Dia. 12 in. to 2.65 lbs./ft. Wall thickness or gauge No. 214. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel, 3 Stainless steel, 5 Fiberglass, 8 RMP (SR), 10 Asbestos-cement, 2 Brass, 4 Galvanized steel, 6 Concrete tile, 9 ABS, 11 Other (specify), 12 None used (open hole). SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot, 3 Mill slot, 5 Gauzed wrapped, 8 Saw cut, 11 None (open hole), 2 Louvered shutter, 4 Key punched, 6 Wire wrapped, 9 Drilled holes, 10 Other (specify). SCREEN-PERFORATED INTERVALS: From 40 ft. to 60 ft., From 18 ft. to 60 ft., GRAVEL PACK INTERVALS: From 18 ft. to 60 ft., From 18 ft. to 60 ft.

6 GROUT MATERIAL: 1 Neat cement, 2 Cement grout, 3 Bentonite, 4 Other. Grout Intervals: From 0 ft. to 10 ft., From 10 ft. to 60 ft., From 10 ft. to 60 ft., From 10 ft. to 60 ft. What is the nearest source of possible contamination: NONE. 1 Septic tank, 4 Lateral lines, 7 Pit privy, 10 Livestock pens, 14 Abandoned water well, 2 Sewer lines, 5 Cess pool, 8 Sewage lagoon, 11 Fuel storage, 15 Oil well/Gas well, 3 Watertight sewer lines, 6 Seepage pit, 9 Feedyard, 12 Fertilizer storage, 16 Other (specify below), 13 Insecticide storage. Direction from well? How many feet?

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-11-84 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 389. This Water Well Record was completed on (mo/day/yr) 7-30-84 under the business name of PEISEN WATER WELL SERV. INC. by (signature) Rudolph J. Peisen.

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.