

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: STAFFORD		S 1/2 NE 1/4 NE 1/4		32		T 24 S		R 13 EW	
Distance and direction from nearest town or city street address of well if located within city?									
ST. JOHN 43/45 WESTSIDE									
2 WATER WELL OWNER: KAW DRILLING CO. INC.					C.C. GLASSCOCK, ST. JOHN, KS.				
RR#, St. Address, Box #: 1010 UNION CENTER					Board of Agriculture, Division of Water Resources				
City, State, ZIP Code: WICHITA, KS 67202					Application Number: T83-464				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:					4 DEPTH OF COMPLETED WELL: 60 ft. ELEVATION:				
					Depth(s) Groundwater Encountered 1. 42 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 17 ft. below land surface measured on mo/day/yr 9-22-83 Pump test data: Well water was ft. after hours pumping gpm Est. Yield 7 gpm; Well water was ft. after hours pumping gpm Bore Hole Diameter 7 7/8 in. to 60 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No				
5 TYPE OF BLANK CASING USED:					CASING JOINTS: Glued X Clamped				
1 Steel 3 RMP (SR) 2 PVC 4 ABS Blank casing diameter 5 in. to 40 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 12 in., weight 265 lbs./ft. Wall thickness or gauge No. 214					5 Wrought iron 8 Concrete tile 6 Asbestos-Cement 9 Other (specify below) 7 Fiberglass 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)				
TYPE OF SCREEN OR PERFORATION MATERIAL:					7 PVC				
1 Steel 3 Stainless steel 5 Fiberglass 2 Brass 4 Galvanized steel 6 Concrete tile SCREEN OR PERFORATION OPENINGS ARE: 48 1 Continuous slot 3 Mill slot 2 Louvered shutter 4 Key punched SCREEN-PERFORATED INTERVALS: From 40 ft. to 60 ft., From ft. to ft., From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 17 ft. to 60 ft., From ft. to ft., From ft. to ft., From ft. to ft.					8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)				
6 GROUT MATERIAL:					5 Gauzed wrapped				
1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 10 ft., From ft. to ft., From ft. to ft., From ft. to ft.					8 Saw cut 11 None (open hole) 9 Drilled holes 10 Other (specify)				
What is the nearest source of possible contamination: NONE					12 Livestock pens 14 Abandoned water well 15 Fuel storage 16 Oil well/Gas well 17 Fertilizer storage 18 Other (specify below) 19 Insecticide storage How many feet?				
Direction from well?									
FROM TO LITHOLOGIC LOG					FROM TO LITHOLOGIC LOG				
0 35 SAND									
35 42 SAND & CLAY									
42 60 GRAVEL									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-22-83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 389 This Water Well Record was completed on (mo/day/yr) 9-29-83 under the business name of PEISER WATER WELL SERV. INC. by (signature) [Signature]									
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.									