

1 LOCATION OF WATER WELL: Fraction	Section Number	Township Number	Range Number
County: Stafford SE 1/4 NW 1/4 NE 1/4	6	T 24 S	R 14 E (W)

Distance and direction from nearest town or city street address of well if located within city?
 Approximately 3 1/4 miles east and 2 3/4 miles north of Macksville

2 WATER WELL OWNER: Roger Murphy
 RR#, St. Address, Box # : 355 NW 30 Ave.
 City, State, ZIP Code : Great Bend, KS 67530
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL 86 ft. ELEVATION: unknown
--	---

Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft. ft.

WELL'S STATIC WATER LEVEL 45.43 ft. below land surface measured on mo/day/yr 6-9-05

Pump test data: Well water was not checked ft. after hours pumping gpm

Est. Yield unknown gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter 9 in. to 86 ft., and in. to ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (specify below)
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well Stock Well

Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yrs sample was submitted Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:

1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped <input checked="" type="checkbox"/>
2 PVC	4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded <input type="checkbox"/>
		7 Fiberglass		Threaded <input type="checkbox"/>

Blank casing diameter 5 in. to 64 ft., Dia in. to ft., Dia in. to ft.

Casing height above land surface 24 in., weight 2.36 lbs./ft. Wall thickness or gauge No .214

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless steel	5 Fiberglass	7 PVC	10 Asbestos-cement
2 Brass	4 Galvanized steel	6 Concrete tile	8 RMP (SR)	11 Other (specify)
			9 ABS	12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify)	ft.

SCREEN-PERFORATED INTERVALS: From 64 ft. to 84 ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 60 ft. to 86 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Bentonite Holeplug Chlorinated Sand

Grout Intervals: From 20 ft. to 55 ft., From 0 ft. to 20 ft., From 55 ft. to 60 ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	None known

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	5	Topsoil			
5	15	Clay, brown			
15	19	Sand and gravel, coarse to fine			
19	42	Clay, brown			
42	45	Sand and gravel, medium to fine			
45	54	Clay, tan and white			
54	61	Sand and gravel, medium to fine with clay streaks			
61	63	Clay, tan			
63	84	Sand and gravel, coarse to fine			
84	86	Clay, gray and white			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6-9-05 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No 185 This Water Well Record was completed on (mo/day/yr) 6-14-05 under the business name of Clarke Well & Equipment, Inc. by (signature) *David W. Clark*