		ORD ; )								S	:	R 14	
		tion from near VILLE, KS.	rest to	en or c	,		of well if		•				
		MRS. Box # : 2601			SE 018			oard of Agr					
City, Sta	te, ZIP c	ode : SALI)	NA, KS	674	<b>1</b> 01-		Aç	oplication !	lumber:				
	LL'S LOCA SECTION	TION WITH Box:			TH OF COMPLE th(s) Ground		L 80 Incountered			2.	ft.	3	. 1
\	1	: : : :	1 1				L 10 ft. Well water					day/yr pumpin	
1	1	; NL			ated Yield	9.0	om: Well wate	er was	ft. after		hours	pumping	) (
			¦ E ¦	Bore H	Hole Diamete	er	8.75 in.	to 80 f	t., and	in.	to	ft.	
	SW	-: SE	1 1	WELL	WATER TO BE	USED AS	6: 01 DOMEST	IC					
/		!!!!	1 1				logical sampl was submitt					disin	fected? \
- !		- ! !											
TYPE OF B Blank cas	LANK CASI	NG USED: 02 PV	VC in. to	o 60	CASING O ft., Dia	G JOINTS	G: GLUED in. to	ft., Dia	in.	to			
TYPE OF B Blank cas Casing he TYPE OF S	CLANK CASI Sing diame Sight abov CCREEN OR	NG USED: 02 P	VC in. to ≥ 12 ATERIAL:	in., : 07 P\ : 08 SA	CASING Oft., Dia Weight VC AW CUT	G JOINTS i 1	G: GLUED in. to lbs/ft. Wall	ft., Dia l thickness	in. 9 or gauge 1	to			
TYPE OF B Blank cas Casing he TYPE OF S SCREEN OR	LANK CASI sing diame right abov CREEN OR R PERFORAT	NG USED: 02 PV ter 5 e land surface PERFORATION M	VC in. to ≥ 12 ATERIAL:	in., : 07 P\ : 08 SA	CASING Oft., Dia Weight VC AW CUT	G JOINTS i 1	G: GLUED in. to lbs/ft. Wall	ft., Dia l thickness	in. 9 or gauge 1	to			
TYPE OF B Blank cas Casing he TYPE OF S SCREEN OR	DLANK CASI sing diame sight abov CCREEN OR R PERFORAT ERFORATED	NG USED: 02 PV ter 5 e land surface PERFORATION M ION OPENINGS (	VC in. to ≥ 12 ATERIAL:	in., : 07 P\ : 08 SA	CASING Oft., Dia Weight VC AW CUT	G JOINTS i 1	G: GLUED in. to lbs/ft. Wall	ft., Dia l thickness	in. 9 or gauge 1	to			
TYPE OF B Blank cas Casing he TYPE OF S SCREEN OR	DLANK CASI sing diame sight abov CCREEN OR R PERFORAT ERFORATED	NG USED: 02 PV ter 5 e land surface PERFORATION M ION OPENINGS	VC in. to ≥ 12 ATERIAL: ARE:	in., : 07 P\ : 08 SA	CASING Oft., Dia Weight VC AW CUT	JOINTS  1  80 f	G: GLUED in. to	ft., Dia l thickness	in. 9 or gauge 1	to			
TYPE OF B Blank cas Casing he TYPE OF S SCREEN OR SCREEN PE GRA GROUT MAT Grout Int	DLANK CASI sing diame sight abov GCREEN OR R PERFORAT ERFORATED AVEL PACK FERIAL FERIAL FERIAL	NG USED: 02 PV ter 5 e land surface PERFORATION M ION OPENINGS A INTERVALS: INTERVALS:  03 BENTONITE From ft	VC in. to	in., in., in., in., in., in., in., in.,	CASING Oft., Dia weight VC AN CUT  60 ft. to ft. to 25 ft. to ft. to	80 f 80 f 80 f	G: GLUED  in. to  lbs/ft. Wall  ft., From  ft., From  ft., From  ft., From	ft., Dia l thickness ft. to ft. to ft. to	in. ft.	to . 26	ft.	many	
TYPE OF B Blank cas Casing he TYPE OF S SCREEN OR SCREEN PE GRA GROUT MAT Grout Int	DLANK CASI Ling diame	NG USED: 02 PV ter 5 e land surface PERFORATION MI ION OPENINGS A INTERVALS: INTERVALS:  03 BENTONITE From ft t source of pu 1? ALL	in. to	in., in., in., in., in., in., in., in.,	CASINE Oft., Dia weight VC AW CUT  60 ft. to ft. to 25 ft. to ft. to ., From mination: CA	80 f 80 f 80 f	G: GLUED  in. to  lbs/ft. Wall  ft., From  ft., From  ft., From  ft., From	ft., Dia l thickness ft. to ft. to ft. to ft. to	in. for gauge for gauge for ft. ft. ft. ft. ft.	to . 26	ft.		feet?
TYPE OF B Blank cas Casing he TYPE OF S SCREEN OR SCREEN PE GRA GROUT MAT Grout Int What is t Direction	DLANK CASI sing diame sight abov GCREEN OR R PERFORAT ERFORATED AVEL PACK ERIAL ervals: the neares from wel 2	NG USED: 02 PV ter 5 e land surface PERFORATION MA ION OPENINGS A INTERVALS: INTERVALS:  03 BENTONITE From ft t source of pu 1? ALL  SILT & SAND	in. to	in., in., in., in., in., in., in., in.,	CASINE Oft., Dia weight VC AW CUT  60 ft. to ft. to 25 ft. to ft. to ., From mination: CA	80 f 80 f 80 f	G: GLUED in. to lbs/ft. Wall ft., From ft., From ft., From ft., From ft., From	ft., Dia l thickness ft. to ft. to ft. to ft. to	in. for gauge for gauge for ft. ft. ft. ft. ft.	to . 26	ft.	many	feet?
TYPE OF B Blank cas Casing he TYPE OF S SCREEN OR SCREEN PE GRA GROUT MAT Grout Int What is t Direction FROM ;	CREEN OR REPORATED  OVEL PACK  CERIAL  CERVALS:  CERVALS	NG USED: 02 PV ter 5 e land surface PERFORATION M ION OPENINGS A INTERVALS: INTERVALS:  03 BENTONITE From ft t source of po 1? ALL  SILT & SAND TAN CLAY	in. to	in., in., in., in., in., in., in., in.,	CASINE Oft., Dia weight VC AW CUT  60 ft. to ft. to 25 ft. to ft. to ., From mination: CA	80 f 80 f 80 f	G: GLUED in. to lbs/ft. Wall ft., From ft., From ft., From ft., From ft., From	ft., Dia l thickness ft. to ft. to ft. to ft. to	in. for gauge for gauge for ft. ft. ft. ft. ft.	to . 26	ft.	many	feet?
TYPE OF B Blank cas Casing he TYPE OF S SCREEN OR SCREEN PE GRA GROUT MAT Grout Int What is t Direction FROM ; 12 ;	DLANK CASI sing diame sight abov CCREEN OR R PERFORAT  ERFORATED  AVEL PACK  ERIAL E	NG USED: 02 PV ter 5 e land surface PERFORATION M ION OPENINGS INTERVALS: INTERVALS:  03 BENTONITE From ft t source of po 1? ALL  SILT & SAND TAN CLAY 05 SAND	in. to	in., in., in., in., in., in., in., in.,	CASINE Oft., Dia weight VC AW CUT  60 ft. to ft. to 25 ft. to ft. to ., From mination: CA	80 f 80 f 80 f	G: GLUED in. to lbs/ft. Wall ft., From ft., From ft., From ft., From ft., From	ft., Dia l thickness ft. to ft. to ft. to ft. to	in. for gauge for gauge for ft. ft. ft. ft. ft.	to . 26	ft.	many	feet?
TYPE OF B Blank cas Casing he TYPE OF S SCREEN OR SCREEN PE GRA GROUT MAT Grout Int What is t Direction FROM ; 12 ; 16 ;	CREEN OR PERFORATED EFFORATED EFFORATED EFFORATED TO 1 12 12 16 127	NG USED: 02 PV ter 5 e land surface PERFORATION M ION OPENINGS INTERVALS: INTERVALS:  O3 BENTONITE From ft t source of po 1? ALL  SILT & SAND TAN CLAY O5 SAND TAN CLAY	vC in. to e 12 ATERIAL:  . to cossible	in., in., in., in., in., in., in., in.,	CASINE Oft., Dia weight VC AW CUT  60 ft. to ft. to 25 ft. to ft. to ., From mination: CA	80 f 80 f 80 f	G: GLUED in. to lbs/ft. Wall ft., From ft., From ft., From ft., From ft., From	ft., Dia l thickness ft. to ft. to ft. to ft. to	in. for gauge for gauge for ft. ft. ft. ft. ft.	to . 26	ft.	many	feet?
TYPE OF B Blank cas Casing he TYPE OF S SCREEN OR SCREEN PE GRA GROUT MAT Grout Int What is t Direction FROM ; 12 ;	DLANK CASI sing diame sight abov CCREEN OR R PERFORAT  ERFORATED  AVEL PACK  ERIAL E	NG USED: 02 PV ter 5 e land surface PERFORATION M ION OPENINGS INTERVALS: INTERVALS:  03 BENTONITE From ft t source of po 1? ALL  SILT & SAND TAN CLAY 05 SAND	vC in. to e 12 ATERIAL:  . to cossible	in., in., in., in., in., in., in., in.,	CASINE Oft., Dia weight VC AW CUT  60 ft. to ft. to 25 ft. to ft. to ., From mination: CA	80 f 80 f 80 f	G: GLUED in. to lbs/ft. Wall ft., From ft., From ft., From ft., From ft., From	ft., Dia l thickness ft. to ft. to ft. to ft. to	in. for gauge for gauge for ft. ft. ft. ft. ft.	to . 26	ft.	many	feet?
TYPE OF B Blank cas Casing he TYPE OF S SCREEN OR SCREEN PE GRA GROUT MAT Grout Int What is t Direction FROM ; 12 ; 16 ;	CREEN OR PERFORATED EFFORATED EFFORATED EFFORATED TO 1 12 12 16 127	NG USED: 02 PV ter 5 e land surface PERFORATION M ION OPENINGS INTERVALS: INTERVALS:  O3 BENTONITE From ft t source of po 1? ALL  SILT & SAND TAN CLAY O5 SAND TAN CLAY	vC in. to e 12 ATERIAL:  . to cossible	in., in., in., in., in., in., in., in.,	CASINE Oft., Dia weight VC AW CUT  60 ft. to ft. to 25 ft. to ft. to ., From mination: CA	80 f 80 f 80 f	G: GLUED in. to lbs/ft. Wall ft., From ft., From ft., From ft., From ft., From	ft., Dia l thickness ft. to ft. to ft. to ft. to	in. for gauge for gauge for ft. ft. ft. ft. ft.	to . 26	ft.	many	feet?
TYPE OF B Blank cas Casing he TYPE OF S SCREEN OR SCREEN PE GRA GROUT MAT Grout Int What is t Direction FROM ; 12 ; 16 ;	CREEN OR PERFORATED EFFORATED EFFORATED EFFORATED TO 1 12 12 16 127	NG USED: 02 PV ter 5 e land surface PERFORATION M ION OPENINGS INTERVALS: INTERVALS:  O3 BENTONITE From ft t source of po 1? ALL  SILT & SAND TAN CLAY O5 SAND TAN CLAY	vC in. to e 12 ATERIAL:  . to cossible	in., in., in., in., in., in., in., in.,	CASINE Oft., Dia weight VC AW CUT  60 ft. to ft. to 25 ft. to ft. to ., From mination: CA	80 f 80 f 80 f	G: GLUED in. to lbs/ft. Wall ft., From ft., From ft., From ft., From ft., From	ft., Dia l thickness ft. to ft. to ft. to ft. to	in. for gauge for gauge for ft. ft. ft. ft. ft.	to . 26	ft.	many	feet?
TYPE OF B Blank cas Casing he TYPE OF S SCREEN OR SCREEN PE GRA GROUT MAT Grout Int What is t Direction FROM ; 12 ; 16 ;	CREEN OR PERFORATED EFFORATED EFFORATED EFFORATED TO 1 12 12 16 127	NG USED: 02 PV ter 5 e land surface PERFORATION M ION OPENINGS INTERVALS: INTERVALS:  O3 BENTONITE From ft t source of po 1? ALL  SILT & SAND TAN CLAY O5 SAND TAN CLAY	vC in. to e 12 ATERIAL:  . to cossible	in., in., in., in., in., in., in., in.,	CASINE Oft., Dia weight VC AW CUT  60 ft. to ft. to 25 ft. to ft. to ., From mination: CA	80 f 80 f 80 f	G: GLUED in. to lbs/ft. Wall ft., From ft., From ft., From ft., From ft., From	ft., Dia l thickness ft. to ft. to ft. to ft. to	in. for gauge for gauge for ft. ft. ft. ft. ft.	to . 26	ft.	many	feet?

Water Well Contractor's License No. 224 This Water Well Record was completed on (ao/day/yr) 09/14/91

under the business name of CARL HAYSE WATER WELL SVC

by (signature)