

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Stafford</u>		<u>NW</u> $\frac{1}{4}$ <u>NW</u> $\frac{1}{4}$ <u>NW</u> $\frac{1}{4}$	<u>22</u>	T <u>24</u> S	R <u>15</u> E <u>(W)</u>
Distance and direction from nearest town or city street address of well if located within city? <u>132 East Broadway, Macksville, Ks.</u>					
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # :		Application Number:			
City, State, ZIP Code :		<u>Macksville, Ks. 67557</u>			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>30'</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered <u>1.18 1/2'</u> ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL <u>19.50</u> ft. below land surface measured on mo/day/yr <u>9-18-97</u>			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter <u>8 1/2"</u> in. to <u>30'</u> ft., and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only <u>10 Monitoring well</u>			
		Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No <u>(No)</u>			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped			
1 Steel 3 RMP (SR)		Welded			
<u>2 PVC</u> 4 ABS		Threaded <u>X</u>			
Blank casing diameter <u>2.375</u> in. to <u>10'</u> ft., Dia. in. to ft., Dia. in. to ft.					
Casing height above land surface <u>Flush Mt.</u> in., weight lbs./ft. Wall thickness or gauge No. <u>S&P-13 Sch 40</u>					
TYPE OF SCREEN OR PERFORATION MATERIAL:		<u>7 PVC</u>			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)		10 Asbestos-cement			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot <u>3 Mill slot</u> 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From <u>30'</u> ft. to <u>10'</u> ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From <u>30'</u> ft. to <u>7 1/2'</u> ft., From ft. to ft.					
6 GROUT MATERIAL:		4 Other ft. From ft. to ft.			
Grout Intervals: From <u>7 1/2'</u> ft. to <u>4'</u> ft., From <u>4'</u> ft. to <u>0'</u> ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy <u>11 Fuel storage</u> <u>Fourier</u> 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage					
Direction from well? <u>South</u>		How many feet? <u>150'</u>			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	.50	Gravel			
.50	5	Dk gray brn-gray clay, stiff.			
5	13	Lt green gray clay w/ caliche stringers & nodules, dry, firm.			
13	16	Lt green sandy clay w/ caliche stringers, dry, faint odor, firm to stiff, fine sand w/ silt matrix.			
16	21	Lt gray silty sand to sand, moist to wet at 18 1/2', very faint odor.			
21	30	Tan-lt rust brn sand, well rounded & sorted, wet, slight odor.			
<u>F.H. OK'd by D. Taylor</u>					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>9-16-97</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>539</u> This Water Well Record was completed on (mo/day/yr) <u>10-8-97</u> under the business name of <u>JB Environmental Drilling</u> by (signature) <u>James Bieber</u>					