

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Stafford</u>		<u>NW 1/4 NW 1/4 NW 1/4</u>	<u>22</u>	T <u>24</u> S	R <u>15</u> E <u>W</u>
Distance and direction from nearest town or city street address of well if located within city? <u>132 East Broadway, Macksville, Ks.</u>					
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # :		Application Number:			
City, State, ZIP Code :					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>30'</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered <u>1.19</u> ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL <u>18.76</u> ft. below land surface measured on mo/day/yr <u>9-18-97</u>			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter <u>8 1/2"</u> in. to <u>30'</u> ft., and in. to ft.			
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only <u>10 Monitoring well</u>			
Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> If yes, mo/day/yr sample was submitted		Water Well Disinfected? Yes No <u>X</u>			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped			
1 Steel 3 RMP (SR)		Welded			
<u>2 PVC</u> 4 ABS		Threaded <u>X</u>			
Blank casing diameter <u>2.375</u> in. to <u>10'</u> ft. Dia in. to ft. Dia in. to ft.		Casing height above land surface <u>Flush Mt.</u> in., weight lbs./ft. Wall thickness or gauge No. <u>SDR-13 Sch 40</u>			
TYPE OF SCREEN OR PERFORATION MATERIAL:		<u>7 PVC</u>			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		10 Asbestos-cement			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		11 Other (specify)			
12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot <u>3 Mill slot</u> 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From <u>30'</u> ft. to <u>10'</u> ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From <u>30'</u> ft. to <u>8'</u> ft., From ft. to ft.					
6 GROUT MATERIAL:		1 Neat cement <u>2</u> Cement grout <u>3</u> Bentonite 4 Other			
Grout Intervals: From <u>8'</u> ft. to <u>4'</u> ft., From <u>4'</u> ft. to <u>0'</u> ft., From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy <u>11</u> Fuel storage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage					
Direction from well? <u>Northwest</u>		How many feet? <u>700'</u>			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	4.50	Grass-med brn sandy clay, firm, damp, earthy odor.			
4.50	11	Med-lt brn sandy clayw/ caliche stringers, damp, friable, firm, no odor, fine sand.			
11	22	Lt brn clayey sand w/ caliche stringers, moist, no odor, firm, friable.			
22	24	Med brn snad, wet, fine grained, well rounded & sorted, no odor.			
24	30	Lt gray clay w/ caliche stiff, no odor, trace of sand, moist.			
F.M. OK'd by Don Taylor					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>9-17-97</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>539</u> This Water Well Record was completed on (mo/day/yr) <u>10-8-97</u> under the business name of <u>JB Environmental Drilling</u> by (signature) <u>James Becker</u>					