

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Stafford</u>		<u>NW 1/4 NW 1/4 NW 1/4</u>	<u>22</u>	T <u>24</u> S	R <u>15</u> EW
Distance and direction from nearest town or city street address of well if located within city?					
<u>132 East Broadway, Macksville, KS.</u>					
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # :		Application Number:			
City, State, ZIP Code :		<u>Macksville, Ks. 67557</u>			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>30'</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. <u>19'</u> ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL <u>17.71</u> ft. below land surface measured on mo/day/yr <u>6-19-98</u>			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm Well water was ft. after hours pumping gpm			
		Bore Hole Diameter <u>8 1/2"</u> in. to <u>30'</u> ft., and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped Welded Threaded X			
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile			
2 PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below)			
Blank casing diameter <u>2.375</u> in. to <u>10'</u> ft., Dia in. to ft., Dia in. to SDR <u>13</u> ft.		7 Fiberglass			
Casing height above land surface <u>Flush Mt.</u> in., weight lbs./ft. Wall thickness or gauge No. <u>SCH 40</u>		TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		10 Asbestos-cement			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		11 Other (specify)			
SCREEN OR PERFORATION OPENINGS ARE:		12 None used (open hole)			
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)		6 Wire wrapped 9 Drilled holes			
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)		SCREEN-PERFORATED INTERVALS:			
From <u>30'</u> ft. to <u>10'</u> ft., From ft. to ft.		From ft. to ft., From ft. to ft.			
GRAVEL PACK INTERVALS:		From <u>30'</u> ft. to <u>8'</u> ft., From ft. to ft.			
From ft. to ft., From ft. to ft.		6 GROUT MATERIAL:			
1 Neat cement 2 Cement grout 3 Bentonite 4 Other		GROUT INTERVALS: From <u>8'</u> ft. to <u>3'</u> ft., From <u>3'</u> ft. to <u>0'</u> ft., From ft. to ft.			
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well		2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)			
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage		Direction from well? <u>East</u> How many feet? <u>8'</u>			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	Concrete			
1	5.5	Dk-med brn sandy clay, moist, low-med plasticity, no odor.			
5.5	10	Red brn clay, moist, no odor, firm to stiff.			
10	19	Red brn-brn clay to sandy clay w/ some caliche stringers & nodules, moist, slight odor, sand, fine-med grained.			
19	30	Brn clayey sand, wet at 19', mod. odor, soft, fine-med grained sand.			
Flush mt. OK'd by Don Taylor					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>6-16-98</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>539</u> This Water Well Record was completed on (mo/day/yr) <u>6-18-98</u> under the business name of <u>JB Environmental Drilling</u> by (signature) <u>James Bieber</u>					