


W.M. WELL & HELLAR ETC.		WATER WELL RECORD		Form WWC-5		KSA 82a-1212			
1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: STAFFORD		C 1/4 E 1/2 1/4 SE 1/4 1/4		2		T 24 S		R 15 EW	
Distance and direction from nearest town or city street address of well if located within city?									
MACKSVILLE 1/2 E 2 N 3/4 E NORTHSIDE									
2 WATER WELL OWNER:		STERLING DRILLING CO.							
RR# St. Address, Box # :		129							
City, State, ZIP Code :		STERLING, KS 67579							
Board of Agriculture, Division of Water Resources		Application Number: T81-926							
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 75 ft. ELEVATION:							
		Depth(s) Groundwater Encountered 1. 55 ft. 2. ft. 3. ft.							
		WELL'S STATIC WATER LEVEL 22 ft. below land surface measured on mo/day/yr 12-9-81							
		Pump test data: Well water was ft. after hours pumping gpm							
		Est. Yield gpm: Well water was ft. after hours pumping gpm							
		Bore Hole Diameter 7 1/8 in. to 7.5 ft. and in. to ft.							
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well							
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)							
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well							
		Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted							
		Water Well Disinfected? Yes No							
5 TYPE OF BLANK CASING USED:		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped							
1 Steel 3 RMP (SR)		6 Asbestos-Cement 9 Other (specify below) Welded							
2 PVC 4 ABS		7 Fiberglass Threaded							
Blank casing diameter 5 in. to 5.5 ft. Dia in. to ft. Dia in. to ft.									
Casing height above land surface 12 in. weight 2.65 lbs./ft. Wall thickness or gauge No. 214									
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement							
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)									
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE: 1/8		5 Gauzed wrapped 8 Saw cut 11 None (open hole)							
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes									
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS: From 5.5 ft. to 7.5 ft. From ft. to ft. From ft. to ft.									
GRAVEL PACK INTERVALS: From 4.5 ft. to 7.5 ft. From ft. to ft. From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other									
Grout Intervals: From 0 ft. to 1.0 ft. From ft. to ft. From ft. to ft.									
What is the nearest source of possible contamination: NONE		10 Livestock pens 14 Abandoned water well							
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well									
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)									
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage									
Direction from well?		How many feet?							
FROM TO LITHOLOGIC LOG		FROM TO LITHOLOGIC LOG							
0 3 SOIL									
3 30 CLAY									
30 35 SAND									
35 55 SANDY CLAY									
55 75 GRAVEL									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-9-81 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 389 This Water Well Record was completed on (mo/day/yr) 12-18-81 under the business name of REISER WATER WELL SERV. INC. by (signature) Rudolph J. Reiser									
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.									