USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

	County	Fraction		Section number		Township number	Range number		
1. Location of well:	Stafford	1/4 NW 1/4 SE	1/4	2	20	r 24 s	R 15	(W)	
Distance and direction from nearest town or city:						Suiter			
Street address of well location if in city:					street: (?) ate, zip code: Macksville, KS 67557				
4. Locate with "X" in section below: Sketch map:					code: [V]	6. Bore hole dia. 24 in.		2-18-75	
N SACION INC.						Well depth 129 ft.			
						7 Cable tool Rotary Driven Dug			
					Hollow rod Jetted Bored X Reverse rotary				
₩ I X E					8. Use: Domestic Public supply Industry X Irrigation Air conditioning Stock		, I		
						Lawn Oil field water Other			
						9. Casing: Material Steel Height: Above or below			
						Threaded Welded X Surface in. RMP PVC Weight _30 . 3 lbs./ft.			
ı→—— ì Mile ———ı						Dia. 16 in. to 60 ft. dep	h.Wall Thickness:_inc	hes or	
5. Type and color of material				From	То	Dia. 16 in. to 109ft. dept	,		
Sandy top soil				0	3	Type Double-slot	_ Dia		
Sandy clay & limestone				3	17	Set between 60 ft. and 100 ft.			
Review S exercised or				17	32	109 ft. and 129 ft. Gravel pack? Yes Size range of material 3/8-200			
Brown & gray clay						11. Static water level:		/day/yr.	
Sand & clay streaks				32	45	13 ft. below land sur			
Brown & gray clay & limestone				45	57	12. Pumping level below land	743 (
				57	65	ft. after h			
Sand, gravel & clay streaks				1 7/	05	Estimated maximum yield		g.p.m.	
Sand & grave1				65	91	13. Water sample submitted: Yes <u>x</u> No 1	mo., Date	/day/yr.	
Brown clay				91	96	14. Well head completion:			
Sand Sanayal				96	99	Pitless adapter	12 Inches above g	rade	
Sand & gravel				1 30	33	15. Well grouted? <u>Yes</u> With: <u>X</u> Neat cement	Bentonite C	oncrete \	
Brown & gray clay & limestone				99	103	Depth: From ft. to .	10ft.		
Cemented gravel, clay & loose gravel				103	113	NONE KNOWN 16. Nearest source of possible	contamination: Fi	eld	
				112	128	ft Direction Well disinfected upon comple		 XNo	
Sand & gravel						17. Pump:	Not installed		
Brown clay			128	129	Manufacturer's name <u>FMC</u> Model number 12MB-5	Corp./Peer	1 11/2		
						Length of drop pipe	ft. capacity 900		
						Type: 60	Tr. Turktur		
				1		Jet	X_ Turbine Recipro	cating \	
ļ	(Use a second si	neet if needed)		<u> </u>		Centrifugal	Other	—— <u>*</u> [/	
18. Elevation: 19. Remarks:					20. Water well contractor's certification: This well was drilled under my jurisdiction and this report				
					is true to the best of my knowledge and belief.				
Topography:							185 × M		
Slope				•	Business name Address <u>Great Bend</u>			7 2	
Upland	Upland Valley					Signed Authorized rep	perentative Date	12-18-7	
	Forward the white, blue and pink copies to the Department of Health and Environment								