

SUITER #1

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: County: STAFFORD

Distance and direction from nearest town or city street address of well if located within city?
MACKEYVILLE 1/2 S 1 3/4 E EASTSIDE

Fraction 1/4 C 1/4 SE 1/4

Section Number 23

Township Number T 24 S

Range Number R 15 E

2 WATER WELL OWNER: BERGMAN DRILLING INC.

RR#, St. Address, Box # 520 UNION CENTER

City, State, ZIP Code WICHITA, KS 67202

D. SUITER, MACKEYVILLE, KS.

Board of Agriculture, Division of Water Resources

Application Number: T84-505

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 75 ft. ELEVATION: 48 ft.

Depth(s) Groundwater Encountered 1. 26 ft. below land surface measured on mo/day/yr 8-4-84

Pump test data: Well water was 7 ft. after 1 hours pumping 7 gpm

Est. Yield 7 gpm; Well water was 7 ft. after 1 hours pumping 7 gpm

Bore Hole Diameter 7 7/8 in. to 75 ft., and 75 in. to 75 ft.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial	7 Lawn and garden only
		10 Observation well
		12 Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:

1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	

Blank casing diameter 5 in. to 55 ft., Dia. 55 in. to 55 ft., Dia. 55 in. to 55 ft.

Casing height above land surface 12 in., weight 2.65 lbs./ft. Wall thickness or gauge No. 214

CASING JOINTS: Glued XX Clamped

Welded

Threaded

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify)
				12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1/8

1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify)	

SCREEN-PERFORATED INTERVALS: From 55 ft. to 75 ft., From ft. to ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 38 ft. to 75 ft., From ft. to ft., From ft. to ft.

6 GROUT MATERIAL:

1 Neat cement	2 Cement grout	3 Bentonite	4 Other
---------------	----------------	-------------	---------

Grout Intervals: From 0 ft. to 10 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination: NONE

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	40	SANDY SOIL			
4	18	CLAY			
18	40	SANDY CLAY			
40	48	CLAY			
48	75	GRAVEL			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-4-84 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 389 This Water Well Record was completed on (mo/day/yr) 8-17-84 under the business name of REISER WATER WELL SERV. INC. by (signature) Paula R. Reiser

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

R

END

SEC.

23

C 1/4 SE 1/4

1/4

60