


BLOOMINGTON #1

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: STAFF		Fraction E 1/2 E 1/2 NE	Section Number 26	Township Number T 24 S	Range Number R 15 EW
County: STAFF Distance and direction from nearest town or city street address of well if located within city?					
MACKSVILLE 1/2 S 2 E 1/4 WESTSIDE					
2 WATER WELL OWNER: J.W. DRILLING CO. INC.					
RR#, St. Address, Box #: 200 E. FIRST SUITE 500					
City, State, ZIP Code: WICHITA, KS 67202					
Board of Agriculture, Division of Water Resources					
Application Number: T82-455					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 75 ft. ELEVATION: 75			
		Depth(s) Groundwater Encountered 1. 25 ft. 2. 3. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 27 ft. below land surface measured on mo/day/yr 8-25-82			
		Pump test data: Well water was 2 ft. after 2 hours pumping 2 gpm			
		Est. Yield 2 gpm: Well water was 2 ft. after 2 hours pumping 2 gpm			
		Bore Hole Diameter 7 7/8 in. to 75 ft. and 75 in. to 75 ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well			
		Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped					
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded					
3 Fiberglass Threaded					
Blank casing diameter 5 in. to 55 ft. Dia 55 in. to 55 ft. Dia 55 in. to 55 ft.					
Casing height above land surface 12 in. weight 2-65 lbs./ft. Wall thickness or gauge No. 214					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)					
12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE: 48					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)					
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes					
7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 55 ft. to 75 ft. From 55 ft. to 75 ft. From 55 ft. to 75 ft.					
GRAVEL PACK INTERVALS: From 45 ft. to 75 ft. From 45 ft. to 75 ft. From 45 ft. to 75 ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 0 ft. to 10 ft. From 0 ft. to 10 ft. From 0 ft. to 10 ft.					
What is the nearest source of possible contamination: NONE					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)					
13 Insecticide storage					
Direction from well? How many feet?					
FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC LOG					
0 4 SOIL					
4 25 CLAY					
25 35 SAND					
35 45 CLAY					
45 55 GRAVEL					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-25-82 and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. 389 This Water Well Record was completed on (mo/day/yr) 9-11-82					
under the business name of PEISER WATER WELLS SERV INC by (signature) R. Peiser					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					