## WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

	County	Fraction	Section	number	Township number Range number
1. Location of well:	Stafford	NE 1/4 NE 1/4/1 1/4		<u>31                                    </u>	1 24 s R 15 EN
	ection from nearest town or city:	MATCHS WILLE R.R.	vner of wel	11: T.R.	Graybill
Street address of well	l location if in City: N 2 5				eawood, Kans. 66206
4. Locate with "X" i		Sketch map:			6. Bore hole dig. 28 in. Completion date 5/4/75
N	N			16	Well depth 95         ft.           7 Cable tool Rotary Driven Dug
1   1			mach	wit	7 Cable tool Rotary Driven Dug Hollow rod Jetted Bored _X_ Reverse rotary
NW	NE		,		8. Use: Domestic Public supply Industry
₩					X Irrigation Air conditioning Stock
sw	SE				Lawn Oil field water Other  9. Casing: Material Transitest: Above or below
					Threaded Welded Surface in.  RMP PVC Weight 30 lbs./ft.
S 1 Mile					RMPPVCWeight_30lbs./ft. Dia.16in. to ft. depth Wall Thickness: inches or
5. Type and color of material			From	То	Diain. to ft. depth gage No
		- V	-		10. Screen: Manufacturer's name Johnson
	Soil		0	2	Type Sawed Dia. 16"
	Clav		2	30	Stot/gauze 3/16 Length Set between ft. and ft.
			1		ft. andft.
	Fine sand		30	40	Gravel pack? Yes Size range of material 1/8-#
	Claay		40	59	11. Static water level: mo./day/yr. 10-5 ft. below land surface Date 9/30/74
Med. sand and gravel			59	95	12. Pumping level below land surfaces:
	Claw	•	0.5	06	
	Clay		1 97	90	Estimated maximum yieldg.p.m.
	MANAGE		+	-	13. Water sample submitted: mo./day/yr.  Yes Po Date
					14. Well head completion:
	E	LEC 500			/
	<b>4</b> , i, //	189			With: Neat cement X Bentonite Concrete
	1 Colortain	<u>u1. 1.7.1.</u>	7	<u> </u>	Depth: From ft. to ft.
Hardness 11. 42 gal			<u> </u>	ļ	16. Negrest source of possible contamination:
Sodain Claud 55.0 PPM					Well disinfected upon completion? YesNo
			' '		17. Pump: Not installed  Manufacturer's name Western I and Roller
ELEC 500 Takolum 19,9 Thadnes 11, 40 gal			†		Model number 42 CM HP 63 Volts
	1 2 1 2 1 2 1 1 1 1 1 1 1 1 1 1 1 1 1 1		-		Length of drop pipe 👉 🗘 ft. capacityg.p.m.   Type:
					Submersible Turbine
	(Use a second s	sheet if needed)			Jet Reciprocating Other
18. Elevation:	19. Remarks:	HATE .	•	•	20. Water well contractor's certification:
		ft. after // hrs. pumping // g.p.m.    17 ft. after // hrs. pumping // g.p.m.   18			
Topography:					
Hill Slope					Business name License No.
Upland					Le se de la lange de la constante de la consta
Valley					Authorized riggesentative