

HAWLEY 6-7

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: EDWARDS	NW 1/4 SW 1/4 NW 1/4	7	T 24 S	R 16 E(W)

Distance and direction from nearest town or city street address of well if located within city?

BELPRE 1 1/2 W 1 3/4 N EASTSIDE

2 WATER WELL OWNER: STERLING DRILLING CO. C.E. HAWLEY LARNEDIKS.	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: 129	Application Number: 781-927
City, State, ZIP Code: STERLING, KS 67579	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 60 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 28 ft. 2. . ft. 3. . ft.
	WELL'S STATIC WATER LEVEL 21 ft. below land surface measured on mo/day/yr 12-9-81
	Pump test data: Well water was . ft. after . hours pumping . gpm
	Est. Yield . gpm Well water was . ft. after . hours pumping . gpm
	Bore Hole Diameter 7 7/8 in. to 60 ft. and . in. to . ft.
	WELL WATER TO BE USED AS:
	5 Public water supply 8 Air conditioning 11 Injection well
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
	Was a chemical/bacteriological sample submitted to Department? Yes . No .; If yes, mo/day/yr sample was submitted
	Water Well Disinfected? Yes . No .

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	10 Asbestos-cement
Blank casing diameter 5 in. to 40 ft. Dia			11 Other (specify)
Casing height above land surface 12 in., weight 265 lbs./ft. Wall thickness or gauge No. 214			12 None used (open hole)
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC		
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE: 1/8		5 Gauzed wrapped	8 Saw cut
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 40 ft. to 60 ft., From			11 None (open hole)
GRAVEL PACK INTERVALS: From 30 ft. to 60 ft., From			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 0 ft. to 10 ft., From				
What is the nearest source of possible contamination: NONE				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well?			13 Insecticide storage	
			How many feet?	

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	5	SOIL			
5	28	SANDY CLAY			
28	60	GRAVEL			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-9-81 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 389 This Water Well Record was completed on (mo/day/yr) 12-18-81 under the business name of REISER WATER WELL SERV. INC. by signature [Signature]

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY
T
29
R
16
EWS
SEC: 7
NW 1/4 SW 1/4 NW 1/4