

USE TYPEWRITER OR BALL POINT PEN—PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and Environment—Division of Environment (Water well Contractors)
Topeka, Kansas 66620

1. Location of well:	County Ewards	Fracture SW 1/4 1/4 1/4	Section number 30	Township number 24 T 24 S	Range number 16 R 16 E/W																								
2. Distance and direction from nearest town or city: 2 West - 3/4 South Street address of well location if in city: OF BELPRE			3. Owner of well: Ed Scheufler R.R. or street: Box 177 City, state, zip code: Larned, KS																										
4. Locate with "X" in section below: N W E S 1 Mile			Sketch map: 6. Bore hole dia. 2 1/2 in. Completion date 6-12-75 Well depth 99 1/2 ft.																										
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th style="width:80%;">5. Type and color of material</th> <th style="width:10%;">From</th> <th style="width:10%;">To</th> </tr> </thead> <tbody> <tr> <td>Sandy Top Soil</td> <td>0</td> <td>7</td> </tr> <tr> <td>Clay</td> <td>7</td> <td>17</td> </tr> <tr> <td>Fine sand & Sandy Clay</td> <td>17</td> <td>37</td> </tr> <tr> <td>Clay</td> <td>37</td> <td>46</td> </tr> <tr> <td>Sand & clay mixed</td> <td>46</td> <td>58</td> </tr> <tr> <td>Good sand & Gravel</td> <td>58</td> <td>100</td> </tr> <tr> <td>HARD Clay</td> <td>100</td> <td>106</td> </tr> </tbody> </table>			5. Type and color of material	From	To	Sandy Top Soil	0	7	Clay	7	17	Fine sand & Sandy Clay	17	37	Clay	37	46	Sand & clay mixed	46	58	Good sand & Gravel	58	100	HARD Clay	100	106	7. Cable tool <input checked="" type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input type="checkbox"/> Reverse rotary		
			5. Type and color of material	From	To																								
			Sandy Top Soil	0	7																								
			Clay	7	17																								
			Fine sand & Sandy Clay	17	37																								
			Clay	37	46																								
			Sand & clay mixed	46	58																								
			Good sand & Gravel	58	100																								
HARD Clay	100	106																											
8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other																													
9. Casing: Material steel Height: above or below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 1 1/8 in. RMP <input type="checkbox"/> PVC <input type="checkbox"/> Weight <input type="checkbox"/> lbs./ft. Dia. 1 1/2 in. to 99 1/2 ft. depth! Wall Thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth! gage No. 7																													
10. Screen: Manufacturer's name Doerr's Type steel Dia. 1 1/2 Slot size 3/16 Length 40 Set between 59 1/2 ft. and 99 1/2 ft. Gravel pack? <input checked="" type="checkbox"/> Size range of material 1/2 3/4 3/8																													
11. Static water level: 30 ft. below land surface Date 4-19-75 mo./day/yr.																													
12. Pumping level below land surfaces: 26 ft. after 1/2 hrs. pumping 1400 g.p.m. <input type="checkbox"/> ft. after <input type="checkbox"/> hrs. pumping <input type="checkbox"/> g.p.m. Estimated maximum yield 1600 g.p.m.																													
13. Water sample submitted: <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No Date 4-29-75 mo./day/yr.																													
14. Well head completion: <input type="checkbox"/> Pitless adapter <input type="checkbox"/> inches above grade																													
15. Well grouted? <input checked="" type="checkbox"/> With: <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft.																													
16. Nearest source of possible contamination: ft. 2 1/2 Direction N Type septic tank Well disinfected upon completion? <input type="checkbox"/> Yes <input type="checkbox"/> No																													
17. Pump: <input type="checkbox"/> Not installed Manufacturer's name Fairbanks Morse Model number 3-m-12 HP 60 Volts <input type="checkbox"/> Length of drop pipe 30 ft. capacity 600 g.p.m. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other																													
18. Elevation:	19. Remarks:		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Rosenkrantz - Bemis 134 Business name License No. Address Great Bend, KS. Signed Fredie Radem Date 9/29/74 Authorized representative																										

24
 R
 16
 W
 30
 Sec
 1/4
 1/4
 1/4

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5