

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Edwards</u>	$\frac{1}{4}$ <u>NC</u> $\frac{1}{4}$ SE	<u>31</u>	T <u>24</u> S	R <u>16</u> EW

Distance and direction from nearest town or city street address of well if located within city?
2 South, 3/4 West of Belpre

2 WATER WELL OWNER: L.B. Adams Jr.
 RR#, St. Address, Box # : Box 127
 City, State, ZIP Code : Belpre, Ks. ~~67519~~ 67519
 Board of Agriculture, Division of Water Resources
 Application Number: 28509

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL <u>90</u> ft. ELEVATION:
	Depth(s) Groundwater Encountered 1 <u>33ft 4"</u> ft. 2 ft. 3 ft.
	WELL'S STATIC WATER LEVEL <u>33ft 4"</u> ft. below land surface measured on <u>mo/day/yr 12-20-04</u>
	Pump test data: Well water was <u>51ft 6"</u> ft. after hours pumping gpm
	Est. Yield <u>1000</u> gpm: Well water was <u>53ft 8"</u> ft. after hours pumping gpm
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) <u>2 Irrigation</u> 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u>; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u>HTH</u> No	

5 TYPE OF BLANK CASING USED:

1 Steel	3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped
2 PVC	4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded
		7 Fiberglass		Threaded

Blank casing diameter 16 in. to 55 ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface 24 in., weight Sch 40 lbs./ft. Wall thickness or guage No.

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 <u>Steel</u>	3 Stainless Steel	5 Fiberglass	7 <u>PVC</u>	10 Asbestos-Cement
2 Brass	4 Galvanized Steel	6 Concrete tile	8 RMP (SR)	11 Other (Specify)
			9 ABS	12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 <u>Continuous slot</u>	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 <u>Louvered shutter</u>	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify)	

SCREEN-PERFORATED INTERVALS: From 90 ft. to 70 ft., From 70 ft. to 55 ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 90 ft. to 20 ft., From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other hole plug

Grout Intervals: From 20 ft. to 0 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	<u>None</u>

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Sandy top soil			
2	11	Brown clay			
11	23	Light brown sandy clay			
23	36	Sand & gravel			
36	39	Brown & gray clay			
39	43	Sand & gravel			
43	49	Clay			
49	89	Sand & gravel			
89	90	Clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-18-05 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 134 This Water Well Record was completed on (mo/day/yr) 2-22-05 under the business name of Rosencrantz- Bemis by (signature) Tom Alby