

[] LOCATION OF WATER WELL: County: EDWARDS Fraction: C ¼ NW ¼ SE ½ Distance and direction from nearest town or city street address of well if located within city? LEWIS 212E 31N WESTSIDE		Section Number: 5 Township Number: T 24 S Range Number: R 17 E()			
[2] WATER WELL OWNER: STERLING DRILLING CO. RR#, St. Address, Box #: BOX 129 City, State, ZIP Code: STERLING, KS 67579		MIKE HATZ, KINSLEY, KS Board of Agriculture, Division of Water Resources Application Number: T84-915			
[3] LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	[4] DEPTH OF COMPLETED WELL: 65 ft. ELEVATION:				
<div style="text-align:center;">N ↑ ---NW---NE--- SWSE ↓ S ← W → E →</div> <div style="font-size: small; margin-top: 5px;">1 Mile ↑</div>	Depth(s) Groundwater Encountered 1. 27 ft. 2. .ft. 3. .ft.				
	WELL'S STATIC WATER LEVEL 23 ft. below land surface measured on mo/day/yr 1. 27.84				
	Pump test data: Well water was .ft. after . hours pumping gpm				
	Est. Yield gpm; Well water was .ft. after . hours pumping gpm				
	Bore Hole Diameter 7.8 in. to 6.5 ft., and .in. to .ft.				
WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below)					
Was a chemical/bacteriological sample submitted to Department? Yes.....No..... If yes, mo/day/yr sample was submitted _____					
Water Well Disinfected? Yes No					
[5] TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 2 PVC 4 ABS Blank casing diameter .5 in. to 4.5 ft., Dia .in. to .ft., Dia .in. to .ft.					
Casing height above land surface .12 in., weight 2.65 lbs./ft. Wall thickness or gauge No. 214					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 7 PNC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)					
SCREEN OR PERFORATION OPENINGS ARE: V8 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes					
SCREEN-PERFORATED INTERVALS: From 4.5 ft. to 6.5 ft., From .ft. to .ft.					
GRAVEL PACK INTERVALS: From 3.5 ft. to 6.5 ft., From .ft. to .ft.					
[6] GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 0 ft. to 1.0 ft., From .ft. to .ft., From .ft. to .ft.					
What is the nearest source of possible contamination: NONE 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? How many feet?					
		LITHOLOGIC LOG			LITHOLOGIC LOG
FROM	TO		FROM	TO	
0	2	TOP SOIL			
2	20	CLAY			
20	25	SANDY CLAY			
25	65	GRAVEL			
[7] CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1. 1. 27. 84 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 3. 89 This Water Well Record was completed on (mo/day/yr) 1. 2. 6. 84 under the business name of REISER WATER WELL SERV INC by signature [Signature]					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send three copies to Kansas Department of Health and Environment, Division of Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					