

OFFICE USE ONLY  
T  
R  
SEC  
23  
NW 1/4 SW 1/4

1 LOCATION OF WATER WELL	Fraction	Section Number	Township Number	Range Number
County: EDWARDS	NW 1/4 NW 1/4 SW 1/4	23	T 24 S	R 17 EW

Distance and direction from nearest town or city? BELPRE 3 1/2 W 1/2 S  
Street address of well if located within city?

2 WATER WELL OWNER: STERLING DRILLING CO  
RR#, St. Address, Box #: 129  
City, State, ZIP Code: STERLING, KS 67579  
Board of Agriculture, Division of Water Resources  
Application Number: T 80-52

3 DEPTH OF COMPLETED WELL: 60 ft. Bore Hole Diameter: 4 in. to 60 ft., and in. to ft.  
Well Water to be used as:  
1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well  
2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
7 Lawn and garden only 10 Observation well  
Well's static water level: 25 ft. below land surface measured on Jan month 25 day 1980 year  
Pump Test Data: Well water was ft. after hours pumping gpm  
Est. Yield gpm: Well water was ft. after hours pumping gpm

4 TYPE OF BLANK CASING USED:  
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile Casing Joints: Glued  Clamped  
2 PVC 4 ABS 7 Fiberglass 9 Other (specify below) Welded  
Blank casing dia: 5 in. to 40 ft., Dia in. to ft., Dia in. to ft.  
Casing height above land surface: 12 in., weight 287.3 lbs./ft. Wall thickness or gauge No. 265  
TYPE OF SCREEN OR PERFORATION MATERIAL:  
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement  
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)  
12 None used (open hole)  
Screen or Perforation Openings Are: V8 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes  
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)  
Screen-Perforation Dia: 5 in. to 60 ft., Dia in. to ft., Dia in. to ft.  
Screen-Perforated Intervals: From 40 ft. to 60 ft., From ft. to ft.  
Gravel Pack Intervals: From 30 ft. to 60 ft., From ft. to ft.

5 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  
Grouted Intervals: From 0 ft. to 10 ft., From ft. to ft., From ft. to ft.  
What is the nearest source of possible contamination: NONE  
1 Septic tank 4 Cess pool 7 Sewage lagoon 10 Fuel storage 14 Abandoned water well  
2 Sewer lines 5 Seepage pit 8 Feed yard 11 Fertilizer storage 15 Oil well/Gas well  
3 Lateral lines 6 Pit privy 9 Livestock pens 12 Insecticide storage 16 Other (specify below)  
13 Watertight sewer lines  
Direction from well: How many feet? Water Well Disinfected? Yes No   
Was a chemical/bacteriological sample submitted to Department? Yes No  If yes, date sample was submitted month day year Pump Installed? Yes No   
If Yes: Pump Manufacturer's name Model No. HP Volts  
Depth of Pump Intake ft. Pumps Capacity rated at gal./min.  
Type of pump: 1 Submersible 2 Turbine 3 Jet 4 Centrifugal 5 Reciprocating 6 Other

6 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on Jan month 25 day 1980 year and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 389  
This Water Well Record was completed on Jan month 31 day 1980 year under the business name of MYERS WATER WELL SERVICE by (signature) Rudolph Meiser

7 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
	0	10	SOIL			
	10	20	SANDY CLAY			
	20	40	CLAY			
	40	60	GRAVEL			

ELEVATION: Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. 4. ft. (Use a second sheet if needed)

INSTRUCTIONS: Use typewriter or ball point pen, please press firmly and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Water Well Contractors, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.