

1 LOCATION OF WATER WELL County: EDWARD	Fraction CENTER 1/4 SE 1/4 SE 1/4	Section Number 33	Township Number T 24 S	Range Number R 17 E
--	--------------------------------------	----------------------	---------------------------	------------------------

Distance and direction from nearest town or city? LEWIS 2 1/2 E 2 S 1 3/4 E NORTHSIDE
Street address of well if located within city?

2 WATER WELL OWNER: STERLING DRILLING CO
RR#, St. Address, Box #: 129
City, State, ZIP Code: STERLING KS 67579
Board of Agriculture, Division of Water Resources
Application Number: T80-35


3 DEPTH OF COMPLETED WELL: 60 ft. Bore Hole Diameter: 9 in. to 60 ft. and in. to ft.
Well Water to be used as:
1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well
2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
7 Lawn and garden only 10 Observation well
Well's static water level: 25' ft. below land surface measured on Jan month 17 day 1980 year
Pump Test Data: NONE Well water was ft. after hours pumping gpm
Est. Yield gpm: Well water was ft. after hours pumping gpm

4 TYPE OF BLANK CASING USED:
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile Casing Joints: Glued XXX Clamped
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
7 Fiberglass Threaded
Blank casing dia: 5 in. to 12.40 ft., Dia in. to ft., Dia in. to ft.
Casing height above land surface: 12.40 in., weight 287.3 lbs./ft. Wall thickness or gauge No. 265
TYPE OF SCREEN OR PERFORATION MATERIAL:
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
Screen or Perforation Openings Are: 1/8 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)
Screen-Perforation Dia: 5 in. to 60 ft., Dia in. to ft., Dia in. to ft.
Screen-Perforated Intervals: From 40 ft. to 60 ft. From ft. to ft. From ft. to ft.
Gravel Pack Intervals: From 30 ft. to 60 ft. From ft. to ft. From ft. to ft.

5 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grouted Intervals: From 0 ft. to 10 ft. From ft. to ft. From ft. to ft.
What is the nearest source of possible contamination: NONE
1 Septic tank 4 Cess pool 7 Sewage lagoon 10 Fuel storage 14 Abandoned water well
2 Sewer lines 5 Seepage pit 8 Feed yard 11 Fertilizer storage 15 Oil well/Gas well
3 Lateral lines 6 Pit privy 9 Livestock pens 12 Insecticide storage 16 Other (specify below)
13 Watertight sewer lines
Direction from well: How many feet? Water Well Disinfected? Yes No
Was a chemical/bacteriological sample submitted to Department? Yes No If yes, date sample was submitted month day year: Pump Installed? Yes No
If Yes: Pump Manufacturer's name Model No. HP Volts
Depth of Pump Intake ft. Pumps Capacity rated at gal./min.
Type of pump: 1 Submersible 2 Turbine 3 Jet 4 Centrifugal 5 Reciprocating 6 Other

6 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on Jan month 17 day 1980 year
and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 389
This Water Well Record was completed on Jan month 19 day 1980 year under the business name of MYERS WATER WELL SERVICE by (signature) Rudolph J. Reiser

7 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:
FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC LOG
0 8 SOIL
8 20 SANDY CLAY
20 40 CLAY
40 60 GRAVELY
ELEVATION:
Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft. 4 ft. (Use a second sheet if needed)



INSTRUCTIONS: Use typewriter or ball point pen, please press firmly and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Water Well Contractors, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY
T 24
R 17
SEC 33
C 1/4 SE 1/4 SE 1/4