1 LOCATION OF WATER WELL: Fraction County: Edwards  Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here  3/4 South 2 Fast of Lewis  Fraction  Number 32  T 24 S R 17 □E  Global Positioning System (GPS) information:  Latitude:	
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here	$\nabla W$
from nearest town or intersection: If at owner's address, check here . Latitude:	<u> </u>
Townstead and the state of the	,
3/4 South, 2 East of Lewis Elevation:	grees)
2 WATER WELL OWNER: Jim Katz  Collection Method:	,
RR#, Street Address, Box #: P.O. Box 202 GPS unit (Make/Model:	
City, State, ZIP Code : Lewis, KS 67552	
3 LOCATE WELL 02	
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 92 ft.	۰
SECTION BOX: Depth(s) Groundwater Encountered (1)	
Pump test data: Well water wasft. afterhours pumping	
EST. YIELD. N/Agpm. Well water was	
W         E   Bore Hole Diameter !!!in. toft., andin. toft.	
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well	
SWSE ☐ Domestic ☐ Feedlot ☐ Oil field water supply ☐ Dewatering ☑ Other (Specify be ☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well Stock	
Was a chemical/bacteriological sample submitted to Department?   Yes   No	
S If yes, mo/day/yr sample was submitted	
1 mile  Water well disinfected? ✓ Yes □ No	-
5 TYPE OF CASING USED: Steel PVC Other	
CASING JOINTS:   ✓ Glued   Clamped   Welded   Threaded	
Casing diameter .5 in. to .92 ft., Diameter in. to ft., Diameter in. to ft.	
Casing height above land surface. 18 in., Weight SDR-26 lbs./ft., Wall thickness or gauge No.	
TYPE OF SCREEN OR PERFORATION MATERIAL:  ☐ Steel ☐ Stainless Steel ✔ PVC ☐ Other (Specify)	
Brass Galvanized Steel None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:	
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)	
□ Louvered shutter □ Key punched □ Wire wrapped ☑ Saw cut □ Other (specify)	
From	
GRAVEL PACK INTERVALS: From 92 ft. to20 ft., From ft. to	
From	
6 GROUT MATERIAL: Neat cement Cement grout Pentonite Other	
Grout Intervals: From	π.
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☑ Other (specify below	
☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Abandoned water well	
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well None  Direction from well	
FROM TO LITHOLOGIC LOG FROM TO LITHO. LOG (cont.) or PLUGGING INTER	JALS
0 6 Sandy top soil	
6 23 Sandy tan clay	<u>-</u>
23 59 Sand & gravel- clean, small to med	
and loose	
59 64 Cemented sand & clay	
64 77 Sand & gravel- clean, small, loose	
77 84 Clay & sand mixed 84 92 Tan clay & caliche	
1 1 1 Clay & Callette	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was   ☐ constructed, ☐ reconstructed, or ☐ plug	ged
under my jurisdiction and was completed on (mo/day/year) .3-7-13 and this record is true to the best of my knowledge and belief.	
Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/year) 3-14-13	
under the business name ofRosencrantz-Bemis by (signature)	
(white, blue, pink) to Kansas Depar tment of Health and E nvironment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 666 12-1367.	
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include <u>fee</u> of \$5.00 for each constructed well. Vi sit us at http://www.kdheks.gov/waterwell/index.html.	
	k Copy