LOCATION OF WATER WELL COUNTY: 024 EDWARDS	: ; Fract	ion 1/4 SW	1/4 NE	1/4	; Section) ; 28	luaber	: Township : T 24	Number S	; Range N ; R 17	umber ₩
Distance and direction 3 E. OF LEWIS, KS	from nearest	town er i	city street	address	of well if)	located wi	thin city?			
WATER WELL OWNER: RR#, St. Address, Box		IHNSON	301		Воа	ard of Agr:	culture, Div	vision of	Water Reso	urces
City, State, ZIP code	: BELPRE,)	(S 67)	519-		App	lication 1	lumber:			
LOCATE WELL'S LOCATION AN "X" IN SECTION BOX:					37 countered			2. Of	t. 3.	0 f
\	!!!	!	S STATIC WAT Pump to	TER LEVEL estdata:	37 ft. b Well water	elow land was (surface meas ft. after	sured on m O hour	o/day/yr s pumping	0 g
1 1 1	1 :	Estima	ated Yield	0 gpm	: Well water	·was () ft. after	0 hour	s pumping	0 g
1	i i	i					., and	in. to	0 ft.	
SW	SE;	1			01 DBMESTIC					
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	¦ Was a ¦ If ye	chemical/ba s, mc/day/ya	acteriolo r sample	gical sample was submitte	e submitter ed	l to departm	ent? No ; Water we	ll disinfe	cted?
:::::::	SED: 05 WROUGH	it IRON	CASIN	JOINTS:	THREADED					
TYPE OF BLANK CASING UBlank casing diameter Casing height above la TYPE OF SCREEN OR PERF SCREEN OR PERFORATION	SED: 05 WROUGH 6 in. ind surface -	 T IRON	CASIN 7 ft., Dia weight ALVANIZED	JOINTS:	THREADED					
TYPE OF BLANK CASING U Blank casing diameter Casing height above la TYPE OF SCREEN OR PERF	SED: 05 WROUGH 6 in. Ind surface or ORATION MATER! OPENINGS ARE: RVALS:	IT IRON to 3: 72 in., From From	CASING 7 ft., Dia weight ALVANIZED ORCH CUT 0 ft. to 0 ft. to 0 ft. to	G JOINTS: in 0 lb 0 ft 0 ft 0 ft	THREADED to 0: s/ft. Wall , From , From , From	ft., Dia thickness O ft. to O ft. to O ft. to	in. to or gauge No 0 ft. 0 ft. 0 ft. 0 ft.			
TYPE OF BLANK CASING U Blank casing diameter Casing height above la TYPE OF SCREEN OR PERF SCREEN OR PERFORATION SCREEN PERFORATED INTE GRAVEL PACK INTE GROUT MATERIAL 03 B Grout Intervals: From What is the nearest so	SED: 05 WROUGH 6 in. ind surface - ORATION MATER! OPENINGS ARE: RVALS: RVALS: ENTONITE 6 ft. to urce of possib	T IRON to 3: 72 in., AL: 04 G 07 T From From From From From	CASING 7 ft., Dia weight ALVANIZED DRCH CUT 0 ft. to 0 ft. to 0 ft. to 0 ft. to	G JOINTS: in 0 lb 0 ft 0 ft 0 ft 0 ft	THREADED to 0 to	ft., Dia thickness Oft. to Oft. to Oft. to Oft. to	in. to or gauge No 0 ft. 0 ft. 0 ft. 0 ft.	0 ft.		a+7
TYPE OF BLANK CASING U Blank casing diameter Casing height above la TYPE OF SCREEN OR PERF SCREEN OR PERFORATION SCREEN PERFORATED INTE GRAVEL PACK INTE GROUT MATERIAL 03 B Grout Intervals: From	SED: 05 WROUGH 6 in. Ind surface - ORATION MATER: OPENINGS ARE: RVALS: RVALS: ENTONITE 6 ft. to surce of possible	T IRON to 3: 72 in., AL: 04 G 07 T From From From From From	CASING 7 ft., Dia weight ALVANIZED ORCH CUT Oft. to Oft. to Oft. to Oft. to Oft. to	G JOINTS: in 0 lb 0 ft 0 ft 0 ft 0 ft	THREADED to 0 to	oft. to oft. to oft. to oft. to	in. to or gauge No O ft. O ft. O ft. O ft. O ft.	0 ft.	ow many fe	et?