


COPY-HP

1 LOCATION OF WATER WELL: County: Edwards Fraction: SE 1/4 NW 1/4 NW 1/4 Section Number: 33 Township Number: T 24 S Range Number: R 19 EW

Distance and direction from nearest town or city street address of well if located within city?
West 3rd Street

2 WATER WELL OWNER: Donna Newcome
RR#, St. Address, Box #: West 3rd St. Board of Agriculture, Division of Water Resources
City, State, ZIP Code: Kinsley, Ks. 67547 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 30 ft. ELEVATION:
Depth(s) Groundwater Encountered 1. 8 ft. 2. 16 ft. 3. 26-83 ft.
WELL'S STATIC WATER LEVEL 16 ft. below land surface measured on mo/day/yr .8-26-83
Pump test data: Well water was NA ft. after NA hours pumping NA gpm
Est. Yield NA gpm: Well water was NA ft. after NA hours pumping NA gpm
Bore Hole Diameter 1.0 in. to 3.0 in. and NA in. to NA in.
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Heat pump
Was a chemical/bacteriological sample submitted to Department? Yes NA No X; If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes HTH No

5 TYPE OF BLANK CASING USED: 1 Steel 2 PVC 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) CASING JOINTS: Glued X Clamped NA Welded NA Threaded NA
Blank casing diameter 5 in. to 10 ft., Dia. NA in. to NA ft., Dia. NA in. to NA ft.
Casing height above land surface 18 in., weight NA lbs./ft. Wall thickness or gauge No. 2.58

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 11 None (open hole) 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 10 ft. to 30 ft., From NA ft. to NA ft., From NA ft. to NA ft.
GRAVEL PACK INTERVALS: From 10 ft. to 30 ft., From NA ft. to NA ft., From NA ft. to NA ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 0 ft. to 10 ft., From NA ft. to NA ft., From NA ft. to NA ft.
What is the nearest source of possible contamination: 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)
Direction from well? west How many feet? 90

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	Top soil			
2	10	Clay			
10	19	Sand and gravel			
19	20	Clay			
20	27	Sand and gravel			
27	30	Yellow Clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-18-83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 134. This Water Well Record was completed on (mo/day/yr) 11-8-83 under the business name of Rosencrantz-Bemis Ent. by (signature) Lora Dodson

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY
T
24
R
19

SEC. 33

SE 1/4 NW 1/4

SW 1/4

20