

1] LOCATION OF WATER WELL: County: Edwards Fraction SE 1/4 SE 1/4 NW 1/4 Section Number 33 Township Number T 24 S Range Number R 19 E/W

Distance and direction from nearest town or city street address of well if located within city? 703 US Highway 56, Kinsley, KS

2] WATER WELL OWNER: Kansas Department of Health and Environment RR#, St. Address, Box #: 1000 SW Jackson City, State, ZIP Code: Topeka, KS Board of Agriculture, Division of Water Resources Application Number:

3] LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram of a 2x2 grid with NW, NE, SW, SE quadrants. An 'X' is in the NW quadrant.] 4] DEPTH OF COMPLETED WELL: 25 ft. ELEVATION: 2172. WELL'S STATIC WATER LEVEL: 11.3 ft. below land surface. Pump test data: Well water was ... gpm. Est. Yield: Well water was ... gpm. WELL WATER TO BE USED AS: 5 Public water supply, 8 Air conditioning, 11 Injection well, 12 Other (Specify below) AS-1. Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yrs sample was submitted Water Well Disinfected? Yes No

5] TYPE OF BLANK CASING USED: 1 Steel, 2 PVC, 3 RMP (SR), 4 ABS, 5 Wrought iron, 6 Asbestos-Cement, 7 Fiberglass, 8 Concrete tile, 9 Other (specify below), CASING JOINTS: Glued, Clamped, Welded, Threaded. Blank casing diameter: 2 in. to 23 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface: Flush Mount in., weight lbs./ft. Wall thickness or gauge No. Sch 40. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel, 2 Brass, 3 Stainless Steel, 4 Galvanized Steel, 5 Fiberglass, 6 Concrete tile, 7 PVC, 8 RMP (SR), 9 ABS, 10 Asbestos-Cement, 11 Other (Specify), 12 None used (open hole). SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot, 2 Louvered shutter, 3 Mill slot, 4 Key punched, 5 Guazed wrapped, 6 Wire wrapped, 7 Torch cut, 8 Saw cut, 9 Drilled holes, 10 Other (specify) ft., 11 None (open hole). SCREEN-PERFORATED INTERVALS: From 23 ft. to 25 ft., From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 21 ft. to 25 ft., From ft. to ft., From ft. to ft.

6] GROUT MATERIAL: 1 Neat cement, 2 Cement grout, 3 Bentonite, 4 Other. Grout intervals: From 1 ft. to 21 ft., From ft. to ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank, 2 Sewer lines, 3 Watertight sewer lines, 4 Lateral lines, 5 Cess pool, 6 Seepage pit, 7 Pit privy, 8 Sewage lagoon, 9 Feedyard, 10 Livestock pens, 11 Fuel storage, 12 Fertilizer storage, 13 Insecticide storage, 14 Abandoned water well, 15 Oil well/Gas well, 16 Other (specify below). Direction from well? On site How many feet? USTs have been removed

Table with columns: FROM, TO, LITHOLOGIC LOG, FROM, TO, PLUGGING INTERVALS. Rows: 0-5 Silt, 5-9 Sand, 9-14 Clay, 14-18 Sand. Includes 'Flush mount waiver for site approved' at the bottom.

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4/16/2010 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 708 This Water Well Record was completed on (mo/day/yr) 5/19/2010 under the business name of Aquaterra Environmental Solutions, Inc by (signature)

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.