		W	ATER WELL RE	CORD	Form	WWC-5	KSA 8	2a-1212 I	D No.	MW-1	10					
			Fraction	on				Section Number			Township Number			Range Number		
	<u>Edwards</u>	***	SE 1		,,	NW		33		T	24	S	R	19	E(W)	
		from nearest to nway 56, Kinsl	wn or city street ey, KS	address	of well	if located	d within city	?								
2 WATE	R WELL OW	NER: Kansas	Department o	f Health	and Er	vironm	ent									
RR#, St. A	ddress, Box	:# : 1000 SV : Topeka	N Jackson KS							App	lication I	Number:			Resources	
			4 DEPTH OF	COMPLE	TED W	ELL	18	ft. ELE	EVATIC)N:∠].	12		•••••		······	
AN "X" I	N SECTION N		Depth(s) Grou	undwater IC WATE	Encoun	itered EL 11.4	1ft. 1	pelow land su	tt. 2 rface n	neasure	d on mo/	ft. 3 dav/vr		•••••	It.	
			P	ump test o	data: \	Well wat	er was		ft. afte	r		hours p	umping		gpm	
-	-NW	- NE	Est. Yield WELL WATER				er was Public wat				ditioning		umping jection v		gpm	
	×		1 Domest	ic 3 l	Feedlot	6	Oil field w	ater eunnly	٥	Dewate	rina	12 0	ther (Sn	acify half	w)	
w -	+ -	— E	2 Irrigation	1 41	ndustria	al 7	Domestic	(lawn & garde	in) (10) Monitoi	nng well .				••••••	
_	-sw	- SE	Was a chemic	al/bacteri	iologica	l camplo	cubmitted	to Departmen	nt? Vac	. N		· If wee m	oldavivr	e campia	wae eub-	
	1		mitted	ai/Dacien	lologica	i sample	Submitted	to Departmen			isinfected		io/day/yii	No No		
5 TYPE	OF BLANK	CASING USED:	<u> </u>	5 Wro	ught iro	n .	8 Cor	ncrete tile		CAS	NG JOIN	ITS: Glue	d	Clampe	d	
1 Stee	əl	3 RMP (S		6 Asb	estos-C	ement	9 Oth	er (specify be				Weld	ed			
②PVC 4 ABS Blank casing diameter			2	7 Fiberglass												
Blank casi	ng diameter ight above is	and surface	fo Flush M	ount in	weight	π., Dia		in. to	lbs	 :/ft Wal	π., Dia I thicknes	ss or auga		n. to ch 40	π.	
Casing height above land surface					, Iri., weight			(7)PVC				stos-Cem		•••••	***************************************	
1 Steel 3 Stainless Steel				5 Fiberglass				8 RMP (SR)								
2 Bra		4 Galvani:		6 Con	crete til		_	ABS				e used (op	•			
	OR PERFO	RATION OPENIA	NGS ARE: /lill slot				zed wrappe wrapped	90		8 Saw o 9 Drilled			11 Non	e (open	nole)	
	vered shutte	\sim	Key punched			7 Toro									ft.	
SCREEN-	PERFORAT	ED INTERVALS	: From	8		ft. to	18	ft., F	rom			ft. to			ft.	
	GDAVEL DA	CK INTERVALS	From	7		ft. to	18	ft., Fi	rom	••••••		ft. to			ft.	
	GNAVELTA	OK HVI EHVALO	From			ft. to		ft., F	rom	••••••	••••••	ft. to			ft.	
GROU	JT MATERIA	II. 1 Nos	it cement	(a)C	ement o	arout	(3)B	entonite	4.0	Other						
			ft. to													
			contamination:					10 Li	vestocl	k pens				ed water		
1 Septic tank 4 Lateral lines				7 Pit privy				_						Oil well/Gas well		
2 Sewer lines 5 Cess pool				8 Sewage la			-	-			•				w)	
3 Watertight sewer lines 6 Seepage pit Direction from well? On site					9 Feedyard			13 Insecticide sto How many feet?				JSTs have been removed				
FROM	TO	JII SILC	LITHOLOG	IC LOG			FROM		l lany i	001; 01		GING IN		S		
0	5	Silt											·····			
5	9	Sand														
9	13.5	Clay														
13.5	18	Sand	W				 		 							
							-	-	┼	· · · · · · · · · · · · · · · · · · ·						
		<u> </u>							ļ							
																
						***************************************		 	1							
		Flush mount waiver for			ite approved											
CONTR	ACTOR'S C	R LANDOWNE	R'S CERTIFIC	ATION: T	his wat	er well v	vas(1)con	structed, (2)	recons	tructed,	or (3)	ged und	ier my ju	ırisdictior	and was	
ompleted (on (mo/day/y	/ear) . 4 / ! 0/ 20 1	0 08		•••••	•••••		and thi	s recor	d is true	to the be	ngt of my kr	owledge	and belie	of. Kansas	
			a Environmen				. MAII UACC	•		nature)	ayiyi) M	18168.18	De la	Ť	······	
		- Aquaten	~ L	-ai colut	, 11				, ,9		7000	40 / K/	//V			