

1] LOCATION OF WATER WELL: County: Harvey Fraction: NE 1/4 NW 1/4 NW 1/4 Section Number: 2 Township Number: T 24 S Range Number: R 2 E 10

Distance and direction from nearest town or city street address of well if located within city? 1 Cedar Dr in Halstead

2] WATER WELL OWNER: Greg Gleason RR#, St. Address, Box #: 1 Cedar Dr City, State, ZIP Code: Halstead, KS 67056 Board of Agriculture, Division of Water Resources Application Number:

3] LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 36-section grid with 'X' in the NW section of the top-left 4-section block]

4] DEPTH OF COMPLETED WELL: 89 ft. ELEVATION: WELL'S STATIC WATER LEVEL: 20 ft. below land surface measured on mo/day/yr 4-17-93 Pump test data: Well water was 26 ft. after 2 hours pumping 25 gpm Est. Yield: gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter: 8 in. to 13 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No

5] TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Threaded Blank casing diameter: 5 in. to 74 ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface: 12 in., weight 237 lbs./ft. Wall thickness or gauge No. 160 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 74 ft. to 89 ft. From ft. to ft. GRAVEL PACK INTERVALS: From 20 ft. to 55 ft. From ft. to ft. From 60 ft. to 89 ft. From ft. to ft.

6] GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 3 ft. to 20 ft. From 55 ft. to 60 ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? SE How many feet? 11

7] CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-17-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 442 This Water Well Record was completed on (mo/day/yr) 4-18-93 under the business name of Miller Drilling by (signature) [Signature]

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.