


1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: HARVEY		SW 1/4 NW 1/4 NE 1/4	15	T 24 S	R 2 EW
Distance and direction from nearest town or city street address of well if located within city? 3 1/2 W of BEAUMONT, KS 24400					
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box #:		Application Number: T-86373			
City, State, ZIP Code:		Wichita, KS 67202			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 66 ft. ELEVATION: 11-14-86			
		Depth(s) Groundwater Encountered 1. 26 ft. 2. 3. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 26 ft. below land surface measured on mo/day/yr 11-14-86			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 11 in. to 66 ft., and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well			
		Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes X No			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued X Clamped			
1 Steel 3 RMP (SR)		Welded			
2 PVC 4 ABS		Threaded			
Blank casing diameter 10 in. to 10 ft., Dia. 1.59 in. to 1.59 ft., Dia.		10 Asbestos-cement			
Casing height above land surface 12 in., weight 1.59 lbs./ft. Wall thickness or gauge No. SPR-26		11 Other (specify)			
TYPE OF SCREEN OR PERFORATION MATERIAL:		12 None used (open hole)			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		10 Asbestos-cement			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		11 Other (specify)			
SCREEN OR PERFORATION OPENINGS ARE:		12 None used (open hole)			
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)		9 Drilled holes			
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS:		From 10 ft. to 66 ft., From 10 ft. to 66 ft.			
GRAVEL PACK INTERVALS:		From 20 ft. to 66 ft., From 20 ft. to 66 ft.			
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 Bentonite 4 Other			
Grout intervals: From 0 ft. to 20 ft., From 20 ft. to 66 ft.		From 0 ft. to 20 ft., From 20 ft. to 66 ft.			
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well		12 Fertilizer storage 16 Other (specify below)			
2 Sewer lines 5 Cess pool 8 Sewage lagoon 13 Insecticide storage		13 Insecticide storage			
3 Watertight sewer lines 6 Seepage pit 9 Feedyard		13 Insecticide storage			
Direction from well?		How many feet? DONE OPENED			
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	TOP SOIL			
2	10	FINE SAND			
10	16	CLAY			
16	38	SAND			
38	54	CLAY			
54	66	SAND			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-14-86 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 5-21-87 under the business name of WENDINGER DRILLING by (signature) Jerome L. Wendinger					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Office of Oil Field and Environmental Geology, Regulation and Permitting Section, Topeka, Kansas 66620-7500, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T 24

R

EW

SEC.

15

SW 1/4

NW 1/4

NE 1/4